

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico
MISCELLANEOUS REPORTS ON WELLS

Submit this report in **TRIPLICATE** to the District Office, Oil Conservation Commission, within **5** days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF	X	REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL		REPORT ON RECOMPLETION OPERATION		REPORT ON (Other)	

July 30, 1956 Monahans, Texas
 (Date) (Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Richardson and Bass State of New Mexico
 (Company or Operator) (Lease)

Richardson and Bass - Rig #28 Well No. 3 in the NE $\frac{1}{4}$ SW $\frac{1}{4}$ of Sec. 8
 (Contractor)

T. 18 S., R. 34 E., NMPM, E K Queen Pool, Lea County.

The Dates of this work were as follows: See detailed account.

Notice of intention to do the work (was) (was not) submitted on Form C-102 on _____, 19____,
 (Cross out incorrect words)

and approval of the proposed plan (was) (was not) obtained.

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

7-26-56 5363' TD Ran Schlumberger laterlog. Ran 144 jts 5 $\frac{1}{2}$ " OD 17# J-55 casing with Baker float shoe and collar. Total of 5365.10'. Less 17.24' cut off - net casing run: 5347.86'. Set at 5362' with centralizers at 4385', 4423', 5226 and 5360'. Cemented with 400 sacks 4% gel and 200 sks regular neat. Plug down at 6:40 AM. Bumped plug with 1300#.

7-27-56 Ran temperature survey - found top cement outside 5 $\frac{1}{2}$ " at 2577' and top of plug at 5294'. Tested casing with 1000# for thirth (30) minutes - held OK.

7-28-56 Drilled cement to 5363' inside casing. Ran Schlumberger GR&N logs. Perforated from 5324' to 5334' with four (4) jet shots per foot.

Witnessed by Frank Raley
Jack D. Semon
 (Name)

Richardson and Bass
Richardson and Bass
 (Company)

Ass't Production Foreman
Engineer
 (Title)

Approved:

OIL CONSERVATION COMMISSION

P. M. Lueder
 (Name)

(Title)

(Date)

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name

Position

Representing

Address

Allan Booth

Ass't Division Office Manager

RICHARDSON AND BASS

Box 1178, Monahans, Texas