

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of notice by checking below:

NOTICE OF INTENTION TO TEST CASING SHUT-OFF		NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL	
NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING	
NOTICE OF INTENTION TO REPAIR WELL		NOTICE OF INTENTION TO PLUG WELL	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO DEEPEN WELL			

Midland, Texas, January 3, 1946

Place

Date

OIL CONSERVATION COMMISSION,
Santa Fe, New Mexico.

Gentlemen:

Following is a notice of intention to do certain work as described below at the _____
 The Texas Company's State of New Mexico "AE" Well No. 1 in NW 1/4 NW 1/4
 Company or Operator 12 Lease 18-S, R. 34-E, N. M. P. M., Vacuum Field,
 of Sec. 12, T. 18-S, R. 34-E, N. M. P. M., Vacuum Field,
 Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK

FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION

As reported on our Form C-103 dated 12-27-45, attempts to recomplate this well as a commercial producer proved unsuccessful. Therefore, we propose to salvage, plug and abandon this well in the following manner. Spot a 30-sack cement plug in bottom of well from 4643' to 4650 and a 25-sack cement plug in bottom of 5 1/2" casing from 4325' to approximately 4150'. Part and pull all possible (approximately 2000') of 5 1/2" casing and spot a cement plug of 30 sacks from 1850' to 1750' (at top of salt.) Spot a 30-sack cement plug from 875' to 775', in bottom of 8 5/8" casing, and plug the top of the hole with 20 sacks of cement. , leaving all 8 5/8" casing cemented in the hole. The hole will be filled with heavy mud between cement plugs and all mud and cement will be pumped in through tubing.

Approved JAN 7 1946, 19_____
 except as follows:

The Texas Company

By [Signature]
 Position Drig. & Prod. Foreman

Send communications regarding well to

Name The Texas CompanyAddress Box 1270Midland, Texas

OIL CONSERVATION COMMISSION,

By [Signature]
 Title CIA & Eng. Dept.