

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☐ other ☐ Dry

2. NAME OF OPERATOR
Mobil Producing TX. & N.M. Inc.

3. ADDRESS OF OPERATOR Nine Greenway Plaza,
Suite 2700, Houston, Texas 77046

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1980' FSL & 660' FWL, Sec 18, T18S, R34E

AT TOP PROD. INTERVAL: Same as surface

AT TOTAL DEPTH: Same as surface

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

☐
☐
☐
☐
☐
☐
☐
☒

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

11-29-84

MIRU Marrs plugging sev. MI unload & rack 2-3/8 WS, perf 5 1/2" csg @ 3050 w/4 JSPF total 4 holes, WIH w/5 1/2" Baker AD-1 Ten pkr on 2-3/8 WS to 2750 displace 5 1/2" csg w/80 bbls 10# Br mud. Set pkr @ 2750, sqz 5 1/2" csg perfs @ 3050 w/40x Cls C cmt, max sqz press 500# w/30x in perfs communicated, Rel pkr & POH SDFN, witnessed by Walter Cox, BLM.

11/31-12/2/84

GIH w/1" sinker bar & tag cmt @ 2488, shot off 5 1/2" csg @ 1861, LD 59 jts 5 1/2" csg, GIH w/2-3/8 tbg OE to 1911, spot 75 x Cls C cmt, POH w/tbg, SDFN.

12-3-84

RIH w/1" Sinker bar, tagged TOC @ 1800', RIH w/2-3/8" tbg OE to 1800' spot 75 x Cls C cmt, POH w/2-3/8 tbg, WOC 3 1/2 hrs, RIH w/1" sinker bar tagged TOC @ 1485, perf 8-5/8" w/4 sqz holes @ 500 & 250', RIH w/2-3/8 tbg OE to 500', (Cont'd on Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft. Back)

18. I hereby certify that the foregoing is true and correct

SIGNED W.B. White TITLE Authorized Agent DATE 12-11-84

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE 9/5/90
CONDITIONS OF APPROVAL, IF ANY:

5. LEASE
USA (LC-065394)
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
Jones-Federal
9. WELL NO.
1
10. FIELD OR WILDCAT NAME
E-K Yates 7-Rivers Queen
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 18, T-18S, R-34E
12. COUNTY OR PARISH
Lea
13. STATE
New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
4000 DF

RECEIVED

SEP 5 10 03 AM '90

RECEIVED

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

17. (Cont'd)
filled 8-5/8" csg w/138/x Cls C cmt from 500 to surface,
POH w/2-3/8" tbgr, NU 8-5/8" swedge, pumped addl 130/x
down 8-5/8" csg, circ cmt to surf behind 8-5/8" csg.
Job compl @ 5:30 pm, TOC @ surf, Walter Cox, BLM
witnessed job.
12-4-84
RD & Rel Marrs csg pullers @ 11:30 am, Walter Cox w/BLM
witnessed job.

RECEIVED

DEC 18 1984

OFFICE
HOLDS OFFICE