Form 9-331a	Approval expires 12-31-30.
(Feb. 1951)	UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY Land Office 165 Cruces 065394-A Unit 3:33

	GICAL SURVEY
<u> </u>	
SUNDRY NOTICES AT	ND REPORTS ON WELLS
NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF.
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	
(INDICATE ABOVE BY CHECK MARK N	NATURE OF REPORT, NOTICE, OR OTHER DATA)
mper Brilling Co., Inc.	
Aid	March 20 90
'ell No. 1 is located 660 ft. from	${N \brace S}$ line and 1980 ft. from ${E \brack W}$ line of sec. 19
W1 RE1 19 188 34E (3/4 Sec. and Sec. No.) (Twp.) (Twp.)	
(Field) (County or	Subdivision) (State of Territory)
	.1:
he elevation of the derrick floor above sea lev	ei is hara It.
	.,,
DETAIL	LS OF WORK
DETAII	LS OF WORK s, weights, and lengths of proposed casings; indicate mudding jobs, cement- her important proposed work)
DETAII	s, weights, and lengths of proposed casings; indicate mudding jobs, cement-
DETAII tate names of and expected depths to objective sands; show size: ing points, and all ot	s, weights, and lengths of proposed casings; indicate mudding jobs, cement- her important proposed work)
DETAIL tate names of and expected depths to objective sands; show size: ing points, and all ot	s, weights, and lengths of proposed casings; indicate mudding jobs, cement- her important proposed work) Oximate total depth of 4500° to test the
DETAIL tate names of and expected depths to objective sands; show size ing points, and all of ropose to drill this well to an approximate a formation. We will run approximately	s, weights, and lengths of proposed casings; indicate mudding jobs, cement- her important proposed work) OXIMATE total depth of 4500° to test the sly 300° of 8 5/8° casing and circulate ceme 4500° of 5 1/2° casing and cement with 400°
DETAIL tate names of and expected depths to objective sands; show size ing points, and all of ropose to drill this well to an approximation. We will run approximate	s, weights, and lengths of proposed casings; indicate mudding jobs, cement- her important proposed work) OXIMATE total depth of 4500° to test the sly 300° of 8 5/8° casing and circulate ceme 4500° of 5 1/2° casing and cement with 400°
DETAIL tate names of and expected depths to objective sands; show size ing points, and all of ropose to drill this well to an approximate a formation. We will run approximately	s, weights, and lengths of proposed casings; indicate mudding jobs, cement- her important proposed work) OXIMATE total depth of 4500° to test the sly 300° of 8 5/8° casing and circulate ceme 4500° of 5 1/2° casing and cement with 400°
DETAIL tate names of and expected depths to objective sands; show size ing points, and all of ropose to drill this well to an approximate a formation. We will run approximately	s, weights, and lengths of proposed casings; indicate mudding jobs, cement- her important proposed work) OXIMATE total depth of 4500° to test the sly 300° of 8 5/8° casing and circulate ceme 4500° of 5 1/2° casing and cement with 400°
DETAIL tate names of and expected depths to objective sands; show size ing points, and all of ropose to drill this well to an approximate a formation. We will run approximately	s, weights, and lengths of proposed casings; indicate mudding jobs, cement- her important proposed work) OXIMATE total depth of 4500° to test the sly 300° of 8 5/8° casing and circulate ceme 4500° of 5 1/2° casing and cement with 400°
DETAIL tate names of and expected depths to objective sands; show size ing points, and all of ropose to drill this well to an approximate a formation. We will run approximately	s, weights, and lengths of proposed casings; indicate mudding jobs, cement- her important proposed work) OXIMATE total depth of 4500° to test the sly 300° of 8 5/8° casing and circulate ceme 4500° of 5 1/2° casing and cement with 400°
DETAIL tate names of and expected depths to objective sands; show size ing points, and all of ropose to drill this well to an approximate a formation. We will run approximately	s, weights, and lengths of proposed casings; indicate mudding jobs, cement- her important proposed work) OXIMATE total depth of 4500° to test the sly 300° of 8 5/8° casing and circulate ceme 4500° of 5 1/2° casing and cement with 400°
DETAIL tate names of and expected depths to objective sands; show size ing points, and all of copose to drill this well to an approximate formation. We will run approximately surface. We will run approximately	s, weights, and lengths of proposed casings; indicate mudding jobs, cement- her important proposed work) OXIMATE total depth of 4500° to test the sly 300° of 8 5/8° casing and circulate ceme 4500° of 5 1/2° casing and cement with 400°
DETAIL tate names of and expected depths to objective sands; show size ing points, and all of copose to drill this well to an approximate formation. We will run approximately of Posmix coment, we Gel and 125 sex	s, weights, and lengths of proposed casings; indicate mudding jobs, cement- her important proposed work) OXIMATE total depth of 4500° to test the sly 300° of 8 5/8° casing and circulate ceme 4500° of 5 1/2° casing and cement with 400°
DETAIL tate names of and expected depths to objective sands; show size ing points, and all of ropose to drill this well to an approximate formation. We will run approximately of Posmix coment, we Gel and 125 sex I understand that this plan of work must receive approval in the same of the same	s, weights, and lengths of proposed casings; indicate mudding jobs, cement-her important proposed work) eximate total depth of 4500° to test the sly 300° of 8 5/8° casing and circulate cement 500° of 5 1/2° casing and cement with 400 of neat cement.
DETAIL tate names of and expected depths to objective sands; show size ing points, and all of ropose to drill this well to an approximate formation. We will run approximately of Posmix coment, 45 Gel and 125 sax I understand that this plan of work must receive approval in the company	s, weights, and lengths of proposed casings; indicate mudding jobs, cement-her important proposed work) contains the total depth of 4500° to test the sly 300° of 8 5/8" casing and circulate cement 500° of 5 1/2° casing and cement with 400 of neat cement. writing by the Geological Survey before operations may be commenced.
DETAIL tate names of and expected depths to objective sands; show size ing points, and all of ropose to drill this well to an approximate formation. We will run approximately of Posmix coment, we Gel and 125 sex I understand that this plan of work must receive approval in the same of the same	s, weights, and lengths of proposed casings; indicate mudding jobs, cement-her important proposed work) Eximate total depth of 4500° to test the sly 300° of 8 5/8" casing and circulate cement 500° of 5 1/2" casing and cement with 400 of next cement. Writing by the Geological Survey before operations may be commenced.

We

U. S. GOVERNMENT PRINTING OFFICE 16-8437-5