

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified 15 to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL	X	NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Odessa, Texas

October 2, 1962

(Place)

(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

Forest Oil Corporation State-Continental

(Company or Operator)

Well No. 1 in JNW 1/4 SE 22 of Sec. 18-S, T. 34-E, R. 34-E, NMPM, Wildcat Pool

(40-acre Subdivision)

Pool

County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

This well was drilled to 10,800' T.D. into the Wolfcamp formation. No commercially productive zones were found.

On 10-2-62 verbal permission was granted by Mr. G. F. Engbrecht to plug and abandon this well as follows: Spot 25 sacks cement at 10,800' (T.D.), 25 sacks at 10,200', 25 sacks at 9400', 25 sacks at 8800', 25 sacks at 7500', 25 sacks at 5800', 25 sacks at 5200, 25 sacks at bottom of 8-5/8" casing (4930'), set a Baker "M" CI bridge plug at 8-5/8" at 3750'. An attempt will be made to recover a possible 3500' of 8-5/8" OD casing, after which a 25 sack plug will be spotted at point of separation, 25 sacks at 1800', 25 sacks at 416' and 10 sacks in top of 13-3/8" OD casing. A steel plate will be welded on top of 13-3/8" casing and a 4" steel marker installed on top of the sealed casing.

Approved....., 19.....
Except as follows:Approved
OIL CONSERVATION COMMISSIONBy.....
Title.....

Forest Oil Corporation

Company or Operator

By.....
Position.....

Send Communications regarding well to:

Name.....
Address.....

4 2