

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT TO DRILL" FORM C-101 FOR SUCH PROPOSALS.)

1. OIL WELL ☒ GAS WELL ☐	5a. Indicate Type of Lease: State ☒ ☐
2. Name of Operator Phillips Petroleum Company	5. State Oil & Gas Lease No. B-1502
3. Address of Operator Room 806, Phillips Building, Odessa, Texas 79761	7. Unit Agreement No. -
4. Location of Well UNIT LETTER D 660 North LINE AND 660 FEET FROM THE West LINE, SECTION 5 RANGELAND 15-S RANGE 35-S N.M.P.M.	8. Term of Lease (Date) Santa Fe, Btry. 2
	9. Well No. 3
	10. Field and Pool, or Well Unit Vacuum (Gb-San Andres)
	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☒	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDON ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOBS ☐	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

(2-8-78)

Swbg. KI Well Units 13 unit. Unable to unseat pump; stripped out rods and tbg. Ran 2-3/8" tbg open end to 4600'. B-J treated down tbg in open hole 4109-4637' w/3500 gals B-J one shot acid containing 25% solvent & 75% of 23% HCl ME acid. Flushed tbg w/ 25 BO, csg w/ 125 bbls. Treated at zero press. Last test 7-12-77, pmpd 24 hrs, 61 BO, no wtr, GOR 2471.

(2-9-78)

Swbgd 9 hrs from 4100', rec 40 BO, no acid wtr. Ran PPCo. BHP bomb.

(2-10-78)

Ran rods & 2" x 1 1/2" x 16' Pmp set 4599'. NO Well Units. Pmpd 18 hrs, no gauge.

(2-11-78)

Pmpd 24 hrs, 109 BO, 32 BO, 6 BAW

(2-12-78)

Pmpd 24 hrs, 119 BO, 10 BAW

(2-13-78)


Pmpd 24 hrs, 115 BO, 1 BW

(2-14-78)

Pmpd 24 hrs, 100 BO, 1 BSW, GOR 1245, 13-66' SPW w/1 1/2" pmp. Single compl in Vacuum (Gb/San Andres) zone perms 4101 - 4637'.

BOF: Series 900, 3000% WP, double w/one set pipe rams, one set blind rams.

18. I hereby certify that the information herein is true and correct to the best of my knowledge and belief.

SIGNED  W. J. Mueller	DATE Engineering Advisor Feb. 15, 1978
APPROVED BY 	DATE FEB
CONDITIONS OF APPROVAL, IF ANY	

FEB 1 2 1979
U.S. DEPARTMENT OF JUSTICE
COMM. ON ASIAN AMERICAN
AFFAIRS, P. 36