

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		5a. Indicate Type of Lease State ☒ Fee ☐
		5. State Oil & Gas Lease No. E6504
1. ☒ OIL WELL ☐ GAS WELL ☐ OTHER		7. Unit Agreement Name Vacuum Abo Unit
2. Name of Operator Phillips Petroleum Company		8. Farm or Lease Name Btry 1
3. Address of Operator Room 806, Phillips Bldg., Odessa, Texas 79761		9. Well No. 3
4. Location of Well UNIT LETTER <u>N</u> <u>660</u> FEET FROM THE <u>south</u> LINE AND <u>1980</u> FEET FROM THE <u>west</u> LINE, SECTION <u>5</u> TOWNSHIP <u>18-S</u> RANGE <u>35-E</u>		10. Field and Pool, or With at Vacuum Abo Reef
11. Elevation (Show whether DF, RT, GR, etc.) 3968' RKB		12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
 TEMPORARILY ABANDON ☐
 PULL OR ALTER CASING ☐
 OTHER ☐

PLUG AND ABANDON ☐
 CHANGE PLANS ☐
 OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☒
 COMMENCE DRILLING OPNS. ☐
 CASING TEST AND CEMENT JOBS ☐
 OTHER Add perfs ☒

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- 4-5-76: MI & RU Ralph's unit, pld rods & tbg. Western perfd 4½" csg w/2 shots/ft. @ 8561-72' 8578-81', 8591-8601', 8612-17', 8642-46', 8683-86', 8696-8710', total 50', 100 holes.
- 4-6-76: Set 2-3/8" tbg & BP at 8715' w/pkr @ 8450'. Howco treated down tbg thru csg perfs 8561-8610' w/5000 gals 28% NE HCL acid w/one ball sealer/bbl. Flshd w/40 BW. Max press 4000#, min 1800#, SITP O#. AIR 4 BPM. Swbd 3 hrs, 30 BLW.
- 4-7-76: Swbd 11 hrs, 66 BO, 78 BL & AW.
- 4-8-76: Swbd 1 hr, 10 BO, Fished for BP, did not recover. Pld tbg & pkr. Ran tbg w/retr tool.
- 4-9-76: Unable to fish BP. Pld tbg & retr tool. Ran tbg w/0.5 and fished BP.
- 4-10-76: Set 2-3/8" tbg w/anchor catcher on btm at 8555, stg npl at 8551'. Set 2"x1¼"x20' pmp at 8551'. Moved out unit. P/16 hrs, no gauge.
- 4-11-76: P/24 hrs, 147 BO, 3 BAW.
- 4-12-76: P/24 hrs, 156 BO, 3 BAW.
- 4-13-76: P/24 hrs, 121 BO, 32 BSW.
- 4-14-76: P/24 hrs, 141 BO, 14 BSW, GOR 1376/1.
- 4-15-18-76: P/96 hrs, no gauge.
- 4-19-76: P/24 hrs, 98 BO, 33 BW, GOR 418/1. Restored to production.

Series 900 BOP, 3000# WP, double w/1 set pipe rams, 1 set blind rams, manually operated.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED W.J. Mueller

TITLE Engineering Advisor

DATE 9-28-76

APPROVED BY Don L. Supv.

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

1976