

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-025-03073
5. Indicate Type of Lease STATE ☒ FEE ☐
6. State Oil & Gas Lease No. B-1838
7. Lease Name or Unit Agreement Name Vacuum Abo Unit Tract 13, Btry 2
8. Well No. 17
9. Pool name or Wildcat Vacuum Abo Reef

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: OIL WELL ☒ GAS WELL ☐ OTHER ☐	
2. Name of Operator Phillips Petroleum Company	
3. Address of Operator 4001 Penbrook Street, Odessa, TX 79762	
4. Well Location Unit Letter <u>0</u> : <u>890</u> Feet From The <u>South</u> Line and <u>2210</u> Feet From The <u>East</u> Line Section <u>5</u> Township <u>18-S</u> Range <u>35-E</u> NMPM <u>Lea</u> County <u></u>	
10. Elevation (Show whether DF, RKB, RT, GR, etc.) <u>3949'</u> GL <u>3964'</u> RKB	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK ☐	REMEDIAL WORK ☒
TEMPORARILY ABANDON ☐	COMMENCE DRILLING OPNS. ☐
PULL OR ALTER CASING ☐	CASING TEST AND CEMENT JOB ☐
OTHER: ☐	OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

8/15/90: Pump 10 bbls of 15% NEFe-11 HCl w/3 gals/1000 corrosion inhibitor & 5 gals/1000 AY-31 surfactant. Pump 1500 gals of 15% NEFe 11 HCl w/3 gals/1000 corrosion inhibitor & 5 gals/1000 AY-31 surfactant.

8/17/90: GIH w/4" csg gun @ 2 JSPF onspiral phasing w/premium deep. Perf 8593'-8600', 7', 14 shots, 8604'-8610', 6', 12 shots, 8646'-8650', 4', 8 shots, 8657'-8670', 13', 26 shots, 30', 60 shots total.

8/18/90: Acidize. Pump 2200 gals 15% NEFe-11 HCl w/3 gals/1000 corrosion inhibitor & 5 gals/1000 AY-31 surfactant.

8/21/90: Pump 2200 gals 15% NEFe 11 HCl w/3 gals/1000 corrosion inhibitor & 5 gals, 1000 AY-31 surfactant.

(over)

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE L. M. Sanders TITLE Supv. Regulation Pro. DATE 7/26/91
TYPE OR PRINT NAME L. M. Sanders TELEPHONE NO. 368-1488

(This space for State Use)

Orig. Signed by
Paul Kautz
Geologist

APPROVED BY

TITLE DATE

CONDITIONS OF APPROVAL, IF ANY:

8/22/90: Swab 3 hrs. Rec 12 BW & 6 B0.

8/23/90: Swab 10 hrs. Rec 8 B0 & 65 BW.

8/24/90: COOH w/pkr & RBP, lay down workstring. Secure well. Temp drop from report. Wait on further evaluation of well.