<u>DISTRICT 1</u> P.O. Box 1980, Hobbs, NM 88241-1980

DISTRICT II

P.O. Box Drawer DD, Artesia, NM 88211-0719

DISTRICT III

1000 Rio Brazos Rd., Aztec, NM 87410

DISTRICT IV P.O. Box 2088, Santa Fe, NM 87504-208 OIL CONSERVATION DIVISION

State of New Mexico

iergy, Minerals and Natural Resources Departmen

P.O. Box 2088

Form C-104 Revised February 10,1994 Instructions on back Submit to Appropriate District Office

5 Copies

+10	Santa Fe, New Mexico 87504-2088		AMENDED REPORT
-2088			
REQUEST FOR AL	LOWABLE AND AUTHORIZATION TO TR	RANSPORT	

TEVA 00 EV	(D) OD 47	•	erator Name a	na Adaress	i				UG	חטא טוא 0223:		
		TION & PRODU	CTION INC.						³ Re		iling Code	
P.O. BOX 73	30, нове	SS, NM 88240						İ			6) EFF. 7/27/	95
	Number 025- 2075	23076			VAC	5 Pool Na		NDRES			⁶ Pool	Code 2180
	roperty Co		⁸ Property Name CENTRAL VACUUM U					NIT .			° We	ell No. 97
10 Surface	ce Locat	ion										
JI or lot no.	Section	Township	Range	Lot.ldn	Fee	et From The	North/So	uth Line	Feet From The	East/V	Vest Line	County
С	6	185	35E	-		660	NOR	RTH	1810	WEST LE		LEA
11 Bottor	m Hole l	ocation			,				· · · · · · · · · · · · · · · · · · ·			
UI or lot no.	Section	Township	Range	Lot.idn	Fee	et From The	The North/South Lin		Feet From The	East/West Line		County
Lse Code S	¹³ Produ	cing Method Code	1	nection Date 3/1/79	1:	⁵ C-129 Perm	Permit Number 16		C-129 Effective Date	17 C-129 Expirat		Expiration Date
l. Oil and	d Gas T	ransporters										
18 Transpor	rter		ransporter Nam	ne		²⁰ PO	D	²¹ O/G	POD ULSTR Location and Description			
015126	6	. ,	L PIPELINE C P.O. BOX 900 LLAS, TX 752)		2484	610	0	LE	A, N.M.	8S-35E (BATTERY UNIT)
022628; 14	4792	(2) TEXAS NE	EW MEXICO F	PIPELINE C	00.	2484	610	0	LE	A, N.M.	8S-35E (BATTERY))
			TTEX 66 PIPE			2484630;2	2806127	G	E 24	-	LEA NM V	
009171	1	40	PM GAS COR 44 PENBROC ESSA, TX 797	K		2484030,	2800127				EA NM SAT	
02234	5	TE: PO BOX 4325,	XACO E & P II		ONS	2807200;	2806128	G	E-31-18S-35E LEA NM VRU			
			TON, TX 7721						F-6-18	S-35E LE	EA NM SAT	T #5
	pod Wat	er	<u> </u>			24 PC	DD ULSTR L	ocation and	d Description			· · · · · · · · · · · · · · · · · · ·
	484650								I. (BATTERY)			
. Well C	ompleti	on Data										
²⁵ S	Spud Date		26 Ready Date	•		²⁷ Total De	pth		²⁸ PBTD		²⁹ Per	forations
30	HOLE SI	ZE	31 CAS	ING & TUBI	NG SIZ	ΣE	32	DEPTH SI	ET	33	SACKS CE	MENT
^{[.} Well T	est Data	<u> </u>										
34 Date N	lew Oll	35 Gas De	elivery Date	³⁶ D	ate of	Test	³⁷ Length	of Test	38 Tubing Pr	еѕѕиге	³⁹ Cas	ing Pressure
40 Choke	e Size	41 Oil	l - Bbls.	⁴² Wa	ter - Bt	ols.	43 Gas - MCF 44 AOF 45 T		45 Tes	st Method		
Division have	e been com	ules and regulations plied with and that th the best of my knowl	e information give				Approve		CONSERVATORIGINAL SIGNI	o ev J	DIVISIO	
Signature	Me	inte ()	inty				Title:					
Printed Name	e !	Monte C. Dunca	n				Title:	ingle description	SEP	19	1995	
	gr Asst		<u> </u>				Approval	Date:_				
	/11/95 hange of op	erator fill in the OGR	Telephor ID number and na		7-041							
				Printe						itle		Date
1	rrevi	ous Operator Sig	ji iatul E	- mile	u Haili				•			

Submit 3 Copies to Appropriate District Office

State of New Mexico Energy, Minerals and Natural Resources Department

DISTRICT

Form C-103 Revised 1-1-89

P.O. Box 1980, Hobbs, NM 88240 P.O. Box 2088 P.O. Box 2088	
DISTRICT II	WELL API NO.
P.O. Drawer DD, Artesia, NM 88210 Santa Fe, New Mexico 87504-2088	30-025-03076
DISTRICT III	5. Indicate Type of Lease STATE X FEE
1000 Rio Brazos Rd., Aztec, NM 87410	
	6. State Oil & Gas Lease No.
SUNDRY NOTICES AND REPORTS ON WELLS	B-1113-1
100 NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEDEN OR DUILD BACK TO	. \\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\
DIFFERENT RESERVOIR, USE APPLICATION FOR PERMIT!	7. Lease Name or Unit Agreement Name
(FORM C-101) FOR SUCH PROPOSALS.)	CENTRAL VACUUM UNIT
1. Type of Well:	
OIL X GAS WELL OTHER	
2. Name of Operator	
Texaco Exploration and Production Inc.	8. Well No.
. Address of Operator	97
P. O. Box 730 Hobbs, NM 88240	9. Pool name or Wildcat
. Well Location	VACUUM GRAYBURG SAN ANDRES
Unit Latter C . 660 r MODTU	
Unit Letter C: 660 Feet From The NORTH Line and	1810 Feet From The WEST
Section	County
Section 6 Township 18-S Range 35-E	NMPM LEA
10. Elevation (Show whether DF, RKB, RT, GR, etc.)	Y/////////////////////////////////////
3989' DF	
1. Check Appropriate Box to Indicate Nature of Notice,	Report or Other Date
NOTICE OF INTENTION TO:	DOES IT TO THE DATA
_	BSEQUENT REPORT OF:
REFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK	[7]
	X ALTERING CASING
MPORARILY ABANDON LI CHANGE PLANS COMMENCE DRILLIN	NG OPNS. 🔲 PLUG AND ABANDONMENT [
JLL OR ALTER CASING	_
CASING TEST AND (CEMENT JOB
THER: OTHER:	r
2. Describe Proceed or Complete Committee Comm	
 Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, incomork). SEE RITE 1103 	luding estimated date of starting any proposed
 Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, inc. work) SEE RULE 1103. 	luding estimated date of starting any proposed
	uding estimated date of starting any proposed
2. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, incowork) SEE RULE 1103. 8/11/93 - 8/15/93	luding estimated date of starting any proposed
8/11/93 - 8/15/93	luding estimated date of starting any proposed
8/11/93 - 8/15/93 . MIRU, TOH W/ PROD EQUIP. C/O TO 4720'.	
8/11/93 - 8/15/93 . MIRU, TOH W/ PROD EQUIP. C/O TO 4720'. . SPTD 650 GALS AMMONIUM BICARRONATE ER 4800', 4705', CET DICE 6.000	
8/11/93 - 8/15/93 . MIRU, TOH W/ PROD EQUIP. C/O TO 4720'. . SPTD 650 GALS AMMONIUM BICARRONATE ER 4800', 4705', CET DICE 6.000	
8/11/93 - 8/15/93 . MIRU, TOH W/ PROD EQUIP. C/O TO 4720'. . SPTD 650 GALS AMMONIUM BICARBONATE FR 4300'-4725', SET PKR @ 387 BICARBONATE INTO FORMATION, SION.	5', SQZD ADDL 650 GALS AMMONIUM
8/11/93 - 8/15/93 . MIRU, TOH W/ PROD EQUIP. C/O TO 4720'. . SPTD 650 GALS AMMONIUM BICARBONATE FR 4300'-4725', SET PKR @ 387 BICARBONATE INTO FORMATION, SION. . SPTD 650 GALS 20% NCL NEFE FR 4300'-4725', SET PKR @ 3975', COTTO	5', SQZD ADDL 650 GALS AMMONIUM
8/11/93 - 8/15/93 . MIRU, TOH W/ PROD EQUIP. C/O TO 4720'. . SPTD 650 GALS AMMONIUM BICARBONATE FR 4300'-4725', SET PKR @ 387 BICARBONATE INTO FORMATION, SION.	5', SQZD ADDL 650 GALS AMMONIUM
8/11/93 - 8/15/93 . MIRU, TOH W/ PROD EQUIP. C/O TO 4720'. . SPTD 650 GALS AMMONIUM BICARBONATE FR 4300'-4725', SET PKR @ 387 BICARBONATE INTO FORMATION, SION. . SPTD 650 GALS 20% NCL NEFE FR 4300'-4725', SET PKR @ 3875', SQZD / SI 1 HR, SWABBED BACK LOAD.	5', SQZD ADDL 650 GALS AMMONIUM ADDL 650 GALS 20% HCL NEFE.
8/11/93 - 8/15/93 . MIRU, TOH W/ PROD EQUIP. C/O TO 4720'. . SPTD 650 GALS AMMONIUM BICARBONATE FR 4300'-4725', SET PKR @ 387 BICARBONATE INTO FORMATION, SION. . SPTD 650 GALS 20% NCL NEFE FR 4300'-4725', SET PKR @ 3875', SQZD / SI 1 HR, SWABBED BACK LOAD.	5', SQZD ADDL 650 GALS AMMONIUM ADDL 650 GALS 20% HCL NEFE.
8/11/93 - 8/15/93 . MIRU, TOH W/ PROD EQUIP. C/O TO 4720'. . SPTD 650 GALS AMMONIUM BICARBONATE FR 4300'-4725', SET PKR @ 387 BICARBONATE INTO FORMATION, SION. . SPTD 650 GALS 20% NCL NEFE FR 4300'-4725', SET PKR @ 3875', SQZD / SI 1 HR, SWABBED BACK LOAD. . ACIDIZED OH FR 4300'-4725' W/ 9000 GALS 20% HCL NEFE. MAX P = 310	5', SQZD ADDL 650 GALS AMMONIUM ADDL 650 GALS 20% HCL NEFE. 0#, AIR = 4.2 BPM.
8/11/93 - 8/15/93 . MIRU, TOH W/ PROD EQUIP. C/O TO 4720'. . SPTD 650 GALS AMMONIUM BICARBONATE FR 4300'-4725', SET PKR @ 387 BICARBONATE INTO FORMATION, SION. . SPTD 650 GALS 20% NCL NEFE FR 4300'-4725', SET PKR @ 3875', SQZD / SI 1 HR , SWABBED BACK LOAD. . ACIDIZED OH FR 4300'-4725' W/ 9000 GALS 20% HCL NEFE. MAX P = 310	5', SQZD ADDL 650 GALS AMMONIUM ADDL 650 GALS 20% HCL NEFE. 0#, AIR = 4.2 BPM.
8/11/93 - 8/15/93 MIRU, TOH W/ PROD EQUIP. C/O TO 4720'. SPTD 650 GALS AMMONIUM BICARBONATE FR 4300'-4725', SET PKR @ 387 BICARBONATE INTO FORMATION, SION. SPTD 650 GALS 20% NCL NEFE FR 4300'-4725', SET PKR @ 3875', SQZD / SI 1 HR, SWABBED BACK LOAD. ACIDIZED OH FR 4300'-4725' W/ 9000 GALS 20% HCL NEFE. MAX P = 310 SCALE SQZD W/ 4 DRUMS TH-793 IN 48 BFW, OVERFLUSHED W/ 860 BFW	5', SQZD ADDL 650 GALS AMMONIUM ADDL 650 GALS 20% HCL NEFE. 0#, AIR = 4.2 BPM.
8/11/93 - 8/15/93 . MIRU, TOH W/ PROD EQUIP. C/O TO 4720'. . SPTD 650 GALS AMMONIUM BICARBONATE FR 4300'-4725', SET PKR @ 387 BICARBONATE INTO FORMATION, SION. . SPTD 650 GALS 20% NCL NEFE FR 4300'-4725', SET PKR @ 3875', SQZD / SI 1 HR, SWABBED BACK LOAD. . ACIDIZED OH FR 4300'-4725' W/ 9000 GALS 20% HCL NEFE. MAX P = 310 SCALE SQZD W/ 4 DRUMS TH-793 IN 48 BFW, OVERFLUSHED W/ 860 BFW OPT 8/29/93 66 BOPD, 581 BWPD, 40 MCFD	5', SQZD ADDL 650 GALS AMMONIUM ADDL 650 GALS 20% HCL NEFE. 0#, AIR = 4.2 BPM.
8/11/93 - 8/15/93 . MIRU, TOH W/ PROD EQUIP. C/O TO 4720'. . SPTD 650 GALS AMMONIUM BICARBONATE FR 4300'-4725', SET PKR @ 387 BICARBONATE INTO FORMATION, SION. . SPTD 650 GALS 20% NCL NEFE FR 4300'-4725', SET PKR @ 3875', SQZD / SI 1 HR, SWABBED BACK LOAD. . ACIDIZED OH FR 4300'-4725' W/ 9000 GALS 20% HCL NEFE. MAX P = 310 SCALE SQZD W/ 4 DRUMS TH-793 IN 48 BFW, OVERFLUSHED W/ 860 BFW OPT 8/29/93 66 BOPD, 581 BWPD, 40 MCFD	5', SQZD ADDL 650 GALS AMMONIUM ADDL 650 GALS 20% HCL NEFE. 0#, AIR = 4.2 BPM.
8/11/93 - 8/15/93 MIRU, TOH W/ PROD EQUIP. C/O TO 4720'. SPTD 650 GALS AMMONIUM BICARBONATE FR 4300'-4725', SET PKR @ 387 BICARBONATE INTO FORMATION, SION. SPTD 650 GALS 20% NCL NEFE FR 4300'-4725', SET PKR @ 3875', SQZD / SI 1 HR, SWABBED BACK LOAD. ACIDIZED OH FR 4300'-4725' W/ 9000 GALS 20% HCL NEFE. MAX P = 310 SCALE SQZD W/ 4 DRUMS TH-793 IN 48 BFW, OVERFLUSHED W/ 860 BFW OPT 8/29/93 66 BOPD, 581 BWPD, 40 MCFD bereby certify that the information alloye is true and complete to the best of my knowledge and belief.	5', SQZD ADDL 650 GALS AMMONIUM ADDL 650 GALS 20% HCL NEFE. 0#, AIR = 4.2 BPM. 7. RETURNED WELL TO PRODUCTION.
8/11/93 - 8/15/93 MIRU, TOH W/ PROD EQUIP. C/O TO 4720'. SPTD 650 GALS AMMONIUM BICARBONATE FR 4300'-4725', SET PKR @ 387 BICARBONATE INTO FORMATION, SION. SPTD 650 GALS 20% NCL NEFE FR 4300'-4725', SET PKR @ 3875', SQZD / SI 1 HR, SWABBED BACK LOAD. ACIDIZED OH FR 4300'-4725' W/ 9000 GALS 20% HCL NEFE. MAX P = 310 SCALE SQZD W/ 4 DRUMS TH-793 IN 48 BFW, OVERFLUSHED W/ 860 BFW OPT 8/29/93 66 BOPD, 581 BWPD, 40 MCFD Marroby certify that the information allowe is true and complete to the best of my knowledge and belief.	5', SQZD ADDL 650 GALS AMMONIUM ADDL 650 GALS 20% HCL NEFE. O#, AIR = 4.2 BPM. 7. RETURNED WELL TO PRODUCTION.
8/11/93 - 8/15/93 MIRU, TOH W/ PROD EQUIP. C/O TO 4720'. SPTD 650 GALS AMMONIUM BICARBONATE FR 4300'-4725', SET PKR @ 387 BICARBONATE INTO FORMATION, SION. SPTD 650 GALS 20% NCL NEFE FR 4300'-4725', SET PKR @ 3875', SQZD ASI 1 HR, SWABBED BACK LOAD. ACIDIZED OH FR 4300'-4725' W/ 9000 GALS 20% HCL NEFE. MAX P = 310 SCALE SQZD W/ 4 DRUMS TH-793 IN 48 BFW, OVERFLUSHED W/ 860 BFW OPT 8/29/93 66 BOPD, 581 BWPD, 40 MCFD SET BY INTELL SPECIAL SASSENATURE AND SET OF THE STATE OF THE S	5', SQZD ADDL 650 GALS AMMONIUM ADDL 650 GALS 20% HCL NEFE. 0#, AIR = 4.2 BPM. 7. RETURNED WELL TO PRODUCTION.
8/11/93 - 8/15/93 MIRU, TOH W/ PROD EQUIP. C/O TO 4720'. SPTD 650 GALS AMMONIUM BICARBONATE FR 4300'-4725', SET PKR @ 387 BICARBONATE INTO FORMATION, SION. SPTD 650 GALS 20% NCL NEFE FR 4300'-4725', SET PKR @ 3875', SQZD ASI 1 HR, SWABBED BACK LOAD. ACIDIZED OH FR 4300'-4725' W/ 9000 GALS 20% HCL NEFE. MAX P = 310 SCALE SQZD W/ 4 DRUMS TH-793 IN 48 BFW, OVERFLUSHED W/ 860 BFW OPT 8/29/93 66 BOPD, 581 BWPD, 40 MCFD SET BY INTELL SPECIAL SASSENATURE AND SET OF THE STATE OF THE S	5', SQZD ADDL 650 GALS AMMONIUM ADDL 650 GALS 20% HCL NEFE. O#, AIR = 4.2 BPM. V. RETURNED WELL TO PRODUCTION. BISTANT DATE 10-6-93
8/11/93 - 8/15/93 . MIRU, TOH W/ PROD EQUIP. C/O TO 4720'. . SPTD 650 GALS AMMONIUM BICARBONATE FR 4300'-4725', SET PKR @ 387 BICARBONATE INTO FORMATION, SION. . SPTD 650 GALS 20% NCL NEFE FR 4300'-4725', SET PKR @ 3875', SQZD ASI 1 HR, SWABBED BACK LOAD. . ACIDIZED OH FR 4300'-4725' W/ 9000 GALS 20% HCL NEFE. MAX P = 310 SCALE SQZD W/ 4 DRUMS TH-793 IN 48 BFW, OVERFLUSHED W/ 860 BFW OPT 8/29/93 66 BOPD, 581 BWPD, 40 MCFD Develop certify that the information allove is true and complete to the best of my knowledge and belief. GNATURE TITLE ENGINEER'S ASSITED TREOR PRINT NAME MONTE C. DUNCAN	5', SQZD ADDL 650 GALS AMMONIUM ADDL 650 GALS 20% HCL NEFE. O#, AIR = 4.2 BPM. 7. RETURNED WELL TO PRODUCTION.
8/11/93 - 8/15/93 MIRU, TOH W/ PROD EQUIP. C/O TO 4720'. SPTD 650 GALS AMMONIUM BICARBONATE FR 4300'-4725', SET PKR @ 387 BICARBONATE INTO FORMATION, SION. SPTD 650 GALS 20% NCL NEFE FR 4300'-4725', SET PKR @ 3875', SQZD / SI 1 HR, SWABBED BACK LOAD. ACIDIZED OH FR 4300'-4725' W/ 9000 GALS 20% HCL NEFE. MAX P = 310 SCALE SQZD W/ 4 DRUMS TH-793 IN 48 BFW, OVERFLUSHED W/ 860 BFW OPT 8/29/93 66 BOPD, 581 BWPD, 40 MCFD Describy contify that the information allows is true and complete to the best of my knowledge and belief. OMATURE TITLE ENGINEER'S ASSUME SPACE for State Use) Orig. Signad has	5', SQZD ADDL 650 GALS AMMONIUM ADDL 650 GALS 20% HCL NEFE. O#, AIR = 4.2 BPM. V. RETURNED WELL TO PRODUCTION. BISTANT DATE 10-6-93
8/11/93 - 8/15/93 . MIRU, TOH W/ PROD EQUIP. C/O TO 4720'. . SPTD 650 GALS AMMONIUM BICARBONATE FR 4300'-4725', SET PKR @ 387 BICARBONATE INTO FORMATION, SION. . SPTD 650 GALS 20% NCL NEFE FR 4300'-4725', SET PKR @ 3875', SQZD / SI 1 HR , SWABBED BACK LOAD. . ACIDIZED OH FR 4300'-4725' W/ 9000 GALS 20% HCL NEFE. MAX P = 310 SCALE SQZD W/ 4 DRUMS TH-793 IN 48 BFW, OVERFLUSHED W/ 860 BFW OPT 8/29/93 66 BOPD, 581 BWPD, 40 MCFD hereby certify that the information above is true and complete to the best of my knowledge and belief. OMATURE TITLE ENGINEER'S ASS OTHEOR PRINT NAME MONTE C. DUNCAN THE RESIDENCE DE STATE Use) OTIG. Signed by Paul Knutter	5', SQZD ADDL 650 GALS AMMONIUM ADDL 650 GALS 20% HCL NEFE. O#, AIR = 4.2 BPM. 7. RETURNED WELL TO PRODUCTION. SISTANT DATE 10-6-93 TELEPHONE NO. 393-7191
8/11/93 - 8/15/93 . MIRU, TOH W/ PROD EQUIP. C/O TO 4720'. . SPTD 650 GALS AMMONIUM BICARBONATE FR 4300'-4725', SET PKR @ 387 BICARBONATE INTO FORMATION, SION. . SPTD 650 GALS 20% NCL NEFE FR 4300'-4725', SET PKR @ 3875', SQZD ASI 1 HR, SWABBED BACK LOAD. . ACIDIZED OH FR 4300'-4725' W/ 9000 GALS 20% HCL NEFE. MAX P = 310 SCALE SQZD W/ 4 DRUMS TH-793 IN 48 BFW, OVERFLUSHED W/ 860 BFW OPT 8/29/93 66 BOPD, 581 BWPD, 40 MCFD THE ENGINEER'S ASS OFFICIE FRINT NAME MONTE C. DUNCAN THE OR FRINT NAME MONTE C. DUNCAN Orig. Signed by Paul Kautz Geologiert TROVED BY TROVED BY TROVED BY	5', SQZD ADDL 650 GALS AMMONIUM ADDL 650 GALS 20% HCL NEFE. O#, AIR = 4.2 BPM. V. RETURNED WELL TO PRODUCTION. BISTANT DATE 10-6-93
MIRU, TOH W/ PROD EQUIP. C/O TO 4720'. SPTD 650 GALS AMMONIUM BICARBONATE FR 4300'-4725', SET PKR @ 387 BICARBONATE INTO FORMATION, SION. SPTD 650 GALS 20% NCL NEFE FR 4300'-4725', SET PKR @ 3875', SQZD / SI 1 HR, SWABBED BACK LOAD. ACIDIZED OH FR 4300'-4725' W/ 9000 GALS 20% HCL NEFE. MAX P = 310. SCALE SQZD W/ 4 DRUMS TH-793 IN 48 BFW, OVERFLUSHED W/ 860 BFW OPT 8/29/93 66 BOPD, 581 BWPD, 40 MCFD SCALE SQZD W/ 4 DRUMS TH-793 IN 48 BFW, OVERFLUSHED W/ 860 BFW OPT 8/29/93 66 BOPD, 581 BWPD, 40 MCFD SCHARLING THIS ENGINEER'S ASS STREOR PRINT NAME MONTE C. DUNCAN This space for State Use) Orig. Signed by Pauli Railty.	5', SQZD ADDL 650 GALS AMMONIUM ADDL 650 GALS 20% HCL NEFE. O#, AIR = 4.2 BPM. 7. RETURNED WELL TO PRODUCTION. SISTANT DATE 10-6-93 TELEPHONE NO. 393-7191