

NEW MEXICO OIL CONSERVATION COMMISSION

Santa, Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of notice by checking below:

NOTICE OF INTENTION TO TEST CASING SHUT-OFF	NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL	
NOTICE OF INTENTION TO CHANGE PLANS	NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING	
NOTICE OF INTENTION TO REPAIR WELL	NOTICE OF INTENTION TO PLUG WELL	X
NOTICE OF INTENTION TO DEEPEN WELL		

Wink, Texas

Place

June 17, 1938

Date

OIL CONSERVATION COMMISSION,
Santa Fe, New Mexico.

Gentlemen:

Following is a notice of intention to do certain work as described below at the

The Texas Company State of New Mexico "P" Well No. **1** in **NW $\frac{1}{4}$ -SE $\frac{1}{4}$**
Company or Operator Lease

of Sec. **7**, T. **18 S.**, R. **35 E.**, N. M. P. M., **Vacuum** Field,
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK

FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION

At the total depth of 4907' the well produced 100% salt water on a bailing test. (Water formation 4905'-4907'). At T.D. 4875' the well swabbed dry and cores below that point show no saturation.

Anticipate plugging this well by plugging back into the 5 $\frac{1}{2}$ " casing with 85 sacks of cement and mudding the hole to the surface. An attempt will then be made to part and pull the 5 $\frac{1}{2}$ " casing at approximately 2700' before spotting a cement plug (10 sacks) near the bottom of the 7-5/8" casing which is cemented at 1638'. After parting and pulling approximately 800' of the 7-5/8" casing, a 4" pipe marker will be cemented in the top of the 10-3/4" surface casing which is cemented at 230' with 200 sacks. This 4" pipe marker will extend 4' above the ground and will be cemented in the top of the hole with 10 sacks of cement.

Approved
except as follows:

JUN 22 1938

19

The Texas Company OFFICE
Company or Operator

By

Position **District Superintendent**
Send communications regarding well to

OIL CONSERVATION COMMISSION,

By

Guy Shepard P. M.

Title **Oil & Gas Inspector**Name **The Texas Company**Address **Drawer K****Wink, Texas.**