

COLL Y		LEA	FIELD Vacuum	STATE NM	OWWO
OPR		TEXACO INC.			MAP
1		State of New Mexico "R" (NCT-4)			3D-025-03099
Sec. 7, T-18-S, R-35-E					CO-ORD
330' fr N Line & 1904' fr W Line of Sec.					
Re-Spud 10-6-64		CLASS			200dP EL 39868
Re-Comp 10-18-64		FORMATION	DATUM	FORMATION	DATUM
CSG & SX - TUBING					
10 3/4" 336' 300					
8 5/8" 3128' 750					
2 7/8" 8832' 1180					
2 7/8" 8836'					
LOGS EL GR RA IND HC A					
		TD 8840', PBD 8799'			

IP San Andres Perfs 4648-97' Swbd 172 BOPD + 16 BW. Pot. Based on 10 hr test of 72 BO + 7 BW.

NOW DUAL COMPLETE W/ABO PERFS 8573-8760'.

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT.	PROP DEPTH	TYPE
DATE		

12-21-64 F.R.C. 12-24-64; OWWO, OTD 8840'.
Orig comp from Drinkard Perfs 7997-8014' & Abo Perfs 8573-8760'.
TD 8840', TD 8799', COMPLETED.
Set CIBP @ 7938' in Drinkard String
Perf (San Andres) @ 4648', 4649', 4650', 4651', 4677', 4679', 4697' W/2 SPI
Ac. 500 gals.
Re-Ac. 1500 gals. 4648-4697'
Frac 15,000 gals oil + 15,000# sd. 4648-4697'.

COUNTY IEA FIELD Vacuum STATE NM MN 03099 WO
 OPR TEXACO INC. MAP
 1 New Mexico 'R' State UT-4
 Sec 7, T-18-S, R-35-E CO-ORD
 330' FNL, 1904' FWL of Sec.

Re-Cmp 2-18-69	CLASS		EL	
	FORMATION	DATUM	FORMATION	DATUM
CSG & SX TUBING				
10 3/4" at 336' w/300 sx				
8 5/8" at 3128' w/75 sx				
2 7/8" at 8832' w/1180 sx.				
2 7/8" at 8836'				
LOGS EL GR RA IND HC A				
TD 8840'; PBD 8550'				

(San Andres) Perfs 4648-97' NO CHANGE.

(Abo) Perfs 8406-8528' NO NEW POTENTIAL.

Distribution limited and publication prohibited by subscribers' agreement.
 Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. PROP DEPTH 8528' TYPE WO
 DATE

3-19-69 F.R.C. 3-21-69
 PD 8528' WO (Abo)
 (Orig. comp 3-7-62 thru (Abo) Perfs 8573-8760'
 & (Drinkard) Perfs 7997-8014', OTD 8840',
 OPB 8799'; OWWO & Re-Cmp 10-18-64 thru (San Andres)
 Perfs 4648-97' & (Abo) Perfs 8573-8760')
 TD 8840'; PBD 8550'; COMPLETE
 BP @ 8550'
 Perf 8518-28' w/2 SPF
 Acid (8518-28') 3000 gals (28%)
 Perf 8406-10', 8426-30' w/2 SPF
 Acid (8406-30') 4000 gals (28%)
 3-21-69 COMPLETION REPORTED