E	STATE OF NEW MEXICO IERGY AND MINERALS DEPARTMEN	ти		
		OIL CONSERVA	TION DIVISION	
	DISTRIBUTION			
	JANTA FE	SANTA FE, NEW		Revised 10-1-73
	FILE	SANTA FE, NEW	MEXICO 87501	· · · · · · · · · · · · · · · · · · ·
	U.S.G.S.			Sa. Indicate Type of Lease
	LAND OFFICE			State X Fee
	OPERATOR			5. State Oll & Gas Lease No.
	have been and the second secon	·		L-6940
	SUNDRY 100 NOT USE THIS FORM FOR PROP USE "APPLICATIO			
1.				7. Unit Agreement Name
	OIL X GAB	OTHER- RE-ENTRY		
2. 1	ame of Operator	8. Farm or Lease Name		
	Yates Petroleum Cor	Reeves ADQ State		
3.7	ddress of Operator	9. Well No.		
	105 South 4th St., A	2		
4.1	ocation of Well	10. Field and Pool, or Wildcat		
	UNIT LETTER H 1	Reeves Penn		
	UNIT LETTER	<u> </u>		
	Fact	N 14 ТОШИВНІР185	255	
	THELINE, SECTION	(1) (1) (1) (1) (1) (1) (1) (1) (1) (1)		
		12. County		
11		3893' GR		Lea
16.	Check A	ppropriate Box To Indicate N	ature of Notice, Report or Ot	her Data
	. NOTICE OF IN	T REPORT OF:		
	•			
PC	FORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WORK	ALTERING CASING
TE	APORARILY ABANDON		COMMENCE DRILLING OPHS.	PLUG AND ABANDONMENT
PU	L OR ALTER CASING	CHANGE PLANS	CASING TEST AND CEMENT JOB	· · · · · · · · · · · · · · · · · · ·
	. —		OTHER Re-Entry & Clea	
	Other			

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1903.

12-15-86. Washed and drilled to top of 5-1/2" casing stub at 4987'. Ran lead block, casing burr up. RIH w/dress-off mill. Cut 2' off 5-1/2" casing stub. POOH. Ran 5-1/2" Bowen lead seal casing patch and 41 jts 5-1/2" casing and casing patch to 4990'. Set patch. NU well head. Ran 122 jts 5-1/2" 15.5# casing and BOP. RIH with concave mill and 14 - 3-1/2" OD drill collars and 2-7/8" tubing. Casing stuck. Drill and mill. Attempt to cut back in casing. Found top of stub. Started cutting. Returns had lots of iron. Cut iron and cement from 7021-31'. Washed down to 9975'. Ran collar log, 14' gap in pipe at 7017-31'. RIH w/bit and 14 - 3-1/4" drill collars into casing stub at 7031'. Pulled to 7003'. Washed to 9975'. Drilled cement to 10167'. Washed to 10716'. Began drilling iron. Drilled 15' iron to 10731'. POOH. Ran lead block, would not go in stub. Ran 4-5/8" overshot with 2-3/8" guide and grapple. Could not get in stub at 7031'.

id. I hereby certify that the information above is true and complete to the best of my knowledge and belief.									
arcito Li amita Dos deux	TITLE _	Production Supervisor	DATE _	1-2-87					
Orig. Signed by Paul Kautz Geologist	TITLE_		DATE_	JAN	7 1987				
CONDITIONS OF APPROVAL, IF ANY:									

