

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from 0 feet to 11,235 feet, and from feet to feet.
Cable tools were used from feet to feet, and from feet to feet.

PRODUCTION

Put to Producing June 12 1958
Test 7-3-58 126
OIL WELL: The production during the first 24 hours was barrels of liquid of which 100 % was
was oil; % was emulsion; % water; and % was sediment. A.P.I.
Gravity 37.4
GAS WELL: The production during the first 24 hours was M.C.F. plus barrels of
liquid Hydrocarbon. Shut in Pressure lbs.
Length of Time Shut in

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico			Northwestern New Mexico		
T. Anhy.	1730'		T. Devonian		T. Ojo Alamo
T. Salt			T. Silurian		T. Kirtland-Fruitland
B. Salt			T. Montoya		T. Farmington
T. Yates	3230'		T. Simpson		T. Pictured Cliffs
T. 7 Rivers			T. McKee		T. Menefee
T. Queen	4420'		T. Ellenburger		T. Point Lookout
T. Grayburg			T. Gr. Wash.		T. Mancos
T. San Andres	4960'		T. Granite		T. Dakota
T. DELAWARE SAND	5738'		T. MISS. LS.	11196'	T. Morrison
T. BONE SPRING	6960'		T.		T. Penn.
T. ABO	8570'		T.		T.
T. WOLF CAMP	9450'		T.		T.
T. STRAWN	10480'		T.		T.
T. Penn.	10904'		T.		T.
T. Miss. CHESTER			T.		T.

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	360	360	Surface rock & shale	5036	5106	70	(continued)
360	1310	950	Redbed & shale	5106	5211	105	Anhydrite & shale
1310	1593	283	Redbed & redrock	5211	7275	2064	Lime & anhydrite
1593	1730	137	Redbed, shale & anhydrite	7275	7714	439	Lime & shale
1730	1816	86	Anhydrite	7714	7731	17	Lime
1816	1893	73	Anhydrite & shale	7731	7768	37	Lime & chert
1893	2073	180	Anhydrite & redbed	7768	7790	22	Lime
2073	2279	206	Anhydrite, gypsum & salt	7790	7908	118	Lime & chert
2279	2589	310	Anhydrite & salt	7908	7974	66	Lime
2589	2773	184	Anhydrite & redbed	7974	8039	65	Lime & chert
2773	2872	99	Anhydrite, gypsum & salt	8039	8064	25	Lime
2872	3037	165	Anhydrite & salt	8064	8350	286	Lime & chert
3037	3124	87	Anhydrite, salt & redbed	8350	8383	33	Lime
3124	3191	67	Anhydrite, gyp. & redbed	8383	8411	28	Lime & chert
3191	3272	81	Anhydrite & shale	8411	8431	20	Lime
3272	3723	451	Anhydrite & gypsum	8431	8470	39	Lime & chert
3723	3740	17	Anhydrite	8470	8480	10	Lime
3740	3953	213	Anhydrite & dolomite	8480	8491	11	Lime & chert
3953	4164	211	Anhydrite & lime	8491	8510	19	Lime
4164	4261	97	Anhydrite, gypsum & lime	8510	8525	15	Shale & lime
4261	4564	303	Anhydrite & lime	8525	8543	18	Lime
4564	4780	216	Lime & shale	8543	8554	11	Shale & lime
4780	4821	41	Anhydrite & lime	8554	8571	17	Lime
4821	4925	104	Lime & shale	8571	8582	11	Shale, sand & lime
4925	5036	111	Lime & anhydrite				Sand
(continued)				(continued)			

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

July 17, 1958

Company or Operator: The Pure Oil Company
Name: J. L. Suttle

Address: P. O. Box 2107, Fort Worth 1, Texas
Position or Title: Chief Clerk

