DISTRIBUTION	Form C-103
	Supersedes Old C-102 and C-103
SANTA FE NEW MEXICO OIL CONSERVATION COMMISSION	Effective 1-1-65
U.S.G.S. (1996)	
U.S.G.S.	a, Indicate Type of Lease
LAND OFFICE	State X Fee
OPERATOR	5. State Oil & Gas Lease No.
	E-1681
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)	
1. OIL X GAS OTHER-	7. Unit Agreement Name
	8. Farm or Lease Name
Union Oil Company of California	Lea "F" State
3. Address of Operator	9. Well No.
P. O. Box 671; Midland, Texas 79701	2
4. Location of well	10. Field and Pool, or Wildcat
UNIT LETTER 0 330 FEET FROM THE SOUTH LINE AND 2180.5 FEET FROM	Vacuum Devonian South
THE East LINE, SECTION 22 TOWNSHIP 18-S RANGE 35-E NAIPHM.	
15. Elevation (Show whether DF, RT, GR, etc.) 2890' SCF	12. County Lea
16. Check Appropriate Box To Indicate Nature of Notice, Report or Othe	r Data
NOTICE OF INTENTION TO: SUBSEQUENT	
PERFORM REMEDIAL WORK PLUG AND ABANDON X REMEDIAL WORK	ALTERING CASING
	PLUG AND ABANDONMENT
TEMPORARILY ABANDON COMMENCE DRILLING OPNS. CHANGE PLANS CASING TEST AND CEMENT JOB	PEGG AND ABANDONMENT
PULL OR ALTER CASING CHANGE PLANS CASING TEST AND CEMENT JOB	
OTHER	
17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including enwork) SEE RULE 1103.	stimated date of starting any proposed
Set bridge plug above perforations 11,532' - 11,590' and cap with 20' Cut and pull 5-1/2" casing from free point.	cement.
Spot cement plugs as follows: 35 sy _ in and out of 5-12/" casing stub.	
35 sx in and out of 5-12/" casing stub,	
35 sx in and out of $5-12/$ " casing stub, 35 sx top of Bone Springs - 6950 ',	
35 sx in and out of 5-12/" casing stub, 35 sx top of Bone Springs - 6950', 35 sx top of San Andres - 4944',	
35 sx in and out of 5-12/" casing stub, 35 sx top of Bone Springs - 6950', 35 sx top of San Andres - 4944', 35 sx in and out of 8-5/8" casing - 3805',	
35 sx in and out of 5-12/" casing stub, 35 sx top of Bone Springs - 6950', 35 sx top of San Andres - 4944', 35 sx in and out of 8-5/8" casing - 3805', 10 sx surface.	
35 sx in and out of 5-12/" casing stub, 35 sx top of Bone Springs - 6950', 35 sx top of San Andres - 4944', 35 sx in and out of 8-5/8" casing - 3805', 10 sx surface. Note: Cement circulated on 8-5/8" casing.	
35 sx in and out of 5-12/" casing stub, 35 sx top of Bone Springs - 6950', 35 sx top of San Andres - 4944', 35 sx in and out of 8-5/8" casing - 3805', 10 sx surface.	
35 sx in and out of 5-12/" casing stub, 35 sx top of Bone Springs - 6950', 35 sx top of San Andres - 4944', 35 sx in and out of 8-5/8" casing - 3805', 10 sx surface. Note: Cement circulated on 8-5/8" casing.	
35 sx in and out of 5-12/" casing stub, 35 sx top of Bone Springs - 6950', 35 sx top of San Andres - 4944', 35 sx in and out of 8-5/8" casing - 3805', 10 sx surface. Note: Cement circulated on 8-5/8" casing.	
35 sx in and out of 5-12/" casing stub, 35 sx top of Bone Springs - 6950', 35 sx top of San Andres - 4944', 35 sx in and out of 8-5/8" casing - 3805', 10 sx surface. Note: Cement circulated on 8-5/8" casing.	
35 sx in and out of 5-12/" casing stub, 35 sx top of Bone Springs - 6950', 35 sx top of San Andres - 4944', 35 sx in and out of 8-5/8" casing - 3805', 10 sx surface. Note: Cement circulated on 8-5/8" casing.	
35 sx in and out of 5-12/" casing stub, 35 sx top of Bone Springs - 6950', 35 sx top of San Andres - 4944', 35 sx in and out of 8-5/8" casing - 3805', 10 sx surface. Note: Cement circulated on 8-5/8" casing.	
35 sx in and out of 5-12/" casing stub, 35 sx top of Bone Springs - 6950', 35 sx top of San Andres - 4944', 35 sx in and out of 8-5/8" casing - 3805', 10 sx surface. Note: Cement circulated on 8-5/8" casing.	
35 sx in and out of 5-12/" casing stub, 35 sx top of Bone Springs - 6950', 35 sx top of San Andres - 4944', 35 sx in and out of 8-5/8" casing - 3805', 10 sx surface. Note: Cement circulated on 8-5/8" casing. Cut off well head, install dry hole marker and clean location.	
35 sx in and out of 5-12/" casing stub, 35 sx top of Bone Springs - 6950', 35 sx top of San Andres - 4944', 35 sx in and out of 8-5/8" casing - 3805', 10 sx surface. Note: Cement circulated on 8-5/8" casing. Cut off well head, install dry hole marker and clean location.	DATE_August 21, 1969
35 sx in and out of 5-12/" casing stub, 35 sx top of Bone Springs - 6950', 35 sx top of San Andres - 4944', 35 sx in and out of 8-5/8" casing - 3805', 10 sx surface. Note: Cement circulated on 8-5/8" casing. Cut off well head, install dry hole marker and clean location.	DATE August 21, 1969

CONDITIONS OF APPROVAL, IF ANY: