## NEW MEXICO OIL CONSERVATION COMMISSION OF FIGE OCC

## MISCELLANEOUS NOTICES APR 22 AM 9 1 58

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

	1	Indicate Nature of Notice by (		0	<del>,</del>
Notice of Intention to Change Plans	N	Notice of Intention to Temporarily Abandon Well		Notice of Intention to Drill Deeper	
Notice of Intention to Plug Well	N	Notice of Intention to Plug Back	x	Notice of Intention to Set Lines	
Notice of Intention to Squeeze	N	Notice of Intention to Acidize		Notice of Intention to Shoot (Nitro)	
Notice of Intention to Gun Perforate	N	Notice of Intention (Other)		Notice of Intention (Other)	
OIL CONSERVATI SANTA FE, NEW M	ION COMMISSION MEXICO	Hobbs, New Mexic	•	April 18,	1958
Gentlemen:					
Following is a N	Notice of Intention to d	o certain work as described below	at the		
aglair oil	(Company or Operato	State Le	<b>a</b> 403	Well Noir	(Unit)
(40-acre Subdivis		, T 188 , R 35	NMPM.	Wildcat	Р
	FIII	L DETAILS OF PROPOSED	DIANO	F WODY	
	(FOLLOW	INSTRUCTIONS IN THE RU	LES AND 1	REGULATIONS)	
	as Lease No.			·	
ria ntt e a					
	3 50001 TD	1 m		1014A As 1048	M and and
OPOSE TO:	15000° TD. (	set 50 sack coment at plug from 12000	plug fi to 121	rom 12340 to 1247 31. Set 5-1/2" 0	O and set D casing
OPOSE TO:	15000' TD. 1 50 sack cemer at 10325' wi	Set 50 sack cement at plug from 12000 th 550 sacks.	plug fi to 121	rom 12340 to 1247 31. Set 5-1/2" 0	O and set D casing
OPOSE TO:	15000' TD. 6 50 sack cemer at 10325' wi	set 50 sack cement at plug from 12000 th 550 sacks.	plug fi to 121	rem 12340 to 1247 31. Set 5-1/2" 0	O and set D casing
OPOSE TO:	15000' TD. 6 50 saek ceme at 10325' wi	set 50 sack cement at plug from 12000 th 550 sacks.	plug fi to 121	rem 12340 to 1247 31. Set 5-1/2" 0	O and set D casing
OPOSE TO:	15000' TD. 1 50 saek ceme at 10325' wi	set 50 sack cement at plug from 12000 th 550 sacks.	plug fi to 121	rom 12340 to 1247 31. Set 5-1/2" 0	O and set D casing
OPOSE TO:	15000' TD. 1 50 sack come at 10325' wi	set 50 sack cement at plug from 12000 th 550 sacks.	plug fr to 121	rcm 12340 to 1247 31. Set 5-1/2" 0	O and set D casing
OPOSE TO:	15000' TD. 1 50 sack cener at 10325' wi	set 50 sack cement at plug from 12000 th 550 sacks.	plug fi to 121	rcm 12340 to 1247 31. Set 5-1/2" 0	O and set D casing
OPOSE TO:	15000' TD. 6 50 sack cene at 10325' wi	set 50 sack cement at plug from 12000 th 550 sacks.	plug fi to 121	rem 12340 to 1247 31. Set 5-1/2° 0	O and set D casing
DPOBE TO:	50 sack come at 10325' wi	at plug from 12000 th 550 sacks.	<b>to</b> 121	31. <b>Set</b> 5-1/2 <b>"</b> 0	D casing
DPOSE TO:	50 sack ceme at 10325' wi	at plug from 12000 th 550 sacks.	<b>to</b> 121	O11 & Gas Compan	D casing
Approved	50 sack come at 10325' wi	at plug from 12000 th 550 sacks.	nelair	O11 & Gas Compan Company of Operator	D casing
Approved	50 sack come at 10325' wi	at plug from 12000 th 550 sacks.	nelair Dist	31. <b>Set</b> 5-1/2 <b>"</b> 0	y casing
Approved	50 sack come at 10325' wi	at plug from 12000 th 550 sacks.	nelair Dist	O11 & Gas Compan Company or Operator Supt.	y casing

Address 520 E Broadway, Hobbs. N.M.