

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

HOBBS OFFICE OCC

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL	<b>XX</b>	NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION  
SANTA FE, NEW MEXICO

Hobbs, New Mexico

August 7, 1958

(Place)

(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

**SINCLAIR OIL & GAS COMPANY**

State Land 403

Well No. 2

Unit

SW 1/4 SW 1/4 of Sec. 22, T. 18S, R. 35E, NMPM, Wildest Pool

Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK

TD 11978'-Devonian (FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS) 460'  
9 5/8"OD Casing @ 4000' w/ 1650# Sk. Cement - Top cement behind Casing 444' f/ surface  
13 3/8"OD Casing @ 332' w/ 400 Sk.-Cement circulated to surface.  
DST#1 f/ 8383 to 8435' Recovered 6700' Salt Water - 123,000 PPM Chloride. No show oil or gas  
DST#2 f/ 8687 to 8740' Recovered 10' Drilling mud- 30 Min. SIP- Zero do  
DST#3 f/ 10747 to 10800' Recovered 10' Drilling mud- 30 Min. SIP 545# do  
DST#4 f/ 11944 to 11978' Recovered 1428' Salt Water 30 Min. SIP 3975# DEVONIAN FORMATION do  
REASON FOR PLUGGING- Dry in DEVONIAN AND BONE SPRINGS FORMATIONS  
Set 25 Sk. cement plug from 11913 to 11978' Keeping hole full heavy mud  
Set 50 " " " " 8321 to 8460' do  
Set 100 " " " " 7100 to 7275' do Drilled out plug to 7134' & tested  
DST#7 f/ 7063 to 7134' Recovered 372' Fresh Water- 30 Min. SIP 2660# Chlorides 1180 PPM. No oil or gas  
Set 25 Sk. cement plug from 7000 to 7134' Keeping hole full heavy mud  
Cut off 9 5/8"OD Casing @ Approx. 460' & Set 25 Sk. cement plug f/ 445' to 475' after spotting  
25 Sk. cement plug f/ 3975 to 4050' in bottom of 9 5/8"OD Casing.  
Set 25 Sk. cement plug f/ 310 to 360' in bottom of 13 3/8"OD Casing-  
Weld steel plate over top of 13 3/8"OD Casing w/ 4" Regulation Marker 4' above surface level-  
Approved..... 19..... PMA Complete

Except as follows:

SINCLAIR OIL & GAS COMPANY

By.....

Position..... Dist. Supt.

Send Communications regarding well to:

Approved  
OIL CONSERVATION COMMISSION

By.....

Name Mr. C. C. Salter - # 520 E. Broadway, Hobbs, N.M.

Title.....

Address.....

Originals - OCC

1cc - State Land Office - Richardson & Bass, Inc - Mr. FHR-HFD-file