

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
OG 5010	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. Unit Agreement Name	
2. Name of Operator Continental Oil Company		8. Farm or Lease Name State KW-23	
3. Address of Operator P. O. Box 460, Hobbs, New Mexico 88240		9. Well No. 1	
4. Location of Well UNIT LETTER A 660 FEET FROM THE North LINE AND 660 FEET FROM THE East LINE, SECTION 23 TOWNSHIP 18S RANGE 35E NMPM.		10. Field and Pool, or Wildcat Reeves Penn. Pool	
15. Elevation (Show whether DF, RT, GR, etc.) 3896 RT		12. County Lea	

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOB ☐
OTHER ☐
ALTERING CASING ☐
PLUG AND ABANDONMENT ☒

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1703.

The well was plugged and abandoned in the following manner:

1. Spotted 50 sacks class "C" cement 10,727-10,302'.
2. Filled hole with mud.
3. Shot 5 1/2" casing at 10,000, 8,514 and 8,306' and failed to pull.
4. Shot 5 1/2" casing at 8,001' and pulled 246 joints.
5. Spotted 25 sacks cement plug at 8,000-7,900, 6,870-6,770, 5,010-4,910 and 3,780-3,680'.
6. Shot 8 5/8" casing at 1,823' and failed to pull.
7. Shot 8 5/8" casing at 343 and pulled 10 joints.
8. Spotted 25 sacks cement 343-300 and 10 sacks cement at surface.
9. Erected dry hole marker.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED _____ TITLE **Sup. Prod. Engineer** DATE **10-24-67**

APPROVED BY **Leshie A. Clements** TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY: _____