

November 1987
Formerly 9-331

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

STANDARD FORM NO. 100-10
OTHER INSTRUCTIONS ON
REVERSE SIDE

Expires August 31, 1988
5. LEASE DESIGNATION AND SERIAL

NM-58164

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Nix "24"

9. WELL NO.

1

10. FIELD AND POOL OR WILDCAT

South Vacuum

11. SEC., T., R., M., OR BLM. AND
SURVEY OR AREA

Sec. 24 T-18-S R-35-E

14. PERMIT NO.

15. ELEVATIONS (Show whether OF, RT, GR, etc.)

3877' GR

12. COUNTY OR PARISH 13. STATE

Lea

NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETION

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

3-24-86 Rigged up and started pulling tubing.

3-25, 29 Continued to pull tubing, pulled 232 joints 3-1/2" 9.3# J-55 tubing and Guiberson L-30 Packer.

3-31 Shot 4 holes in 5-1/2" casing at 10,730'. Set cement retainer at 10,670'. Ran in hole with 340 jts. (10,670') 2-3/8" tubing. Tested in hole at 6000 psi above slips. Sting into retainer, pumped 5 bbls water to catch pressure. Pumped 20 bbls at 800 psi. Pulled out of retainer and pumped 235 bbls 10# mud in 5-1/2" casing to load hole, at 2 bpm at 400 psi.

4-1 Pumped 5 bbls water at 0 - 200 psi at 1.5 bpm. Pumped 75 sacks (15.73 bbls) of 15.6 lb/gal type "H" cement at 0 - 500 psi.

4-2 Ran free point and worked casing. Free point at 5900'. 5% free at 6000', 95% free at 5900'. Pulled out of hole and ran back in with gauge ring. Hit object at 6800', pushed object to 8000'. Pulled out of hole with gauge ring and ran in with 5-1/2" scraper and 2-3/8" tubing to 9700'

Page 1 of 3

18. I hereby certify that the foregoing is true and correct

SIGNED

J. R. Hughes

TITLE

Dist. Drlg. Supt.

DATE

7-30-87

(This space for Federal or State office use)

ACCEPTED FOR RECORD

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

AUG 13 1987

SJS

*See Instructions on Reverse Side

CARLSBAD, NEW MEXICO