

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL	X	NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
 SANTA FE, NEW MEXICO

Hobbs, New Mexico
 (Place)

January 9, 1962
 (Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

The Pure Oil Company Reeves "A" Well No. 3-26 in 0
 (Company or Operator) Lease (Unit)
SW 1/4 SE 1/4 of Sec. 26, T. 18S, R. 35E, NMPM, South Vacuum Devonian Pool
 (40-acre Subdivision)
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK
 (FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

At present the well has 5-1/2" casing set at 10,170' cemented w/115 sacks cement, the top of cement behind the pipe is 8,950'. 8-5/8" casing set at 3,801' w/1469 sacks cement, returns to surface. 11-3/4" casing set at 453' w/475 sacks cement, returns to surface. TD of well 12,004'. Cement plugs are set 11,842'-12,004' w/45 sacks and 10,200'-10,350' w/45 sacks.

It is proposed to cut and pull the 5-1/2" casing at 8,800', then place a 25 sack cement plug 47' inside the 5-1/2" with the top of cement at 8,729'. Cement plugs w/20 sacks would then be placed above the Abo at 8,509'-8,570', above the Delaware at 5,700'-5,761', above the San Andres at 4,850'-4,911' and at the base of the 8-5/8" casing from 3,770'-3,840'. A 10 sack cement plug will be placed at the surface, with 4-1/2" CD pipe welded to the surface cap to serve as marker. Hole will be filled with mud laden fluid.

Approved....., 19.....
 Except as follows:

Approved
 OIL CONSERVATION COMMISSION

By.....
 Title.....

The Pure Oil Company
 Company or Operator

By.....H. G. Teague.....H. G. Teague

Position.....District Superintendent.....
 Send Communications regarding well to:

Name.....Mr. H. G. Teague.....

Address.....P. O. Box 1777 - Hobbs, New Mexico.....