

## OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below:

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL	<b>X</b>		

Midland, Texas

May 28, 1945

Place

Date

OIL CONSERVATION COMMISSION,  
SANTA FE, NEW MEXICO.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the

**The Texas Company's J. P. Reeves** Well No. **1** in the  
Company or Operator Lease

**NW 1/4 Sec. 26** of Sec. **26**, T. **18-S**, R. **35-E**, N. M. P. M.,  
**Wilcox** Field, **Lee** County.

The dates of this work were as follows: (See below)

Notice of intention to do the work was ~~(insert)~~ submitted on Form C-102 on **April 25** 19 **45**  
and approval of the proposed plan was ~~(insert)~~ obtained. (Cross out incorrect words.)

## DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

This well was drilled to total depth of 5655', encountering salt water only, and has been salvaged, plugged and abandoned in the following manner. Cement plugs were spotted as follows: 45 sacks, 5655-5535'; 20 sacks, 5350-5300'; 30 sacks, 3450-3370' (at base of salt); and 30 sacks, 1870-1800' at top of salt and in bottom of 9-5/8" casing). The 9-5/8" casing was parted and pulled at 698'. A cement plug of 30 sacks was spotted in the bottom of the 13-3/8" casing from 315 to 275' and the required 4" pipe marker was cemented in the top of the hole with  
(See reverse side)

Witnessed by \_\_\_\_\_ Name \_\_\_\_\_ Company **The Texas Company** Title \_\_\_\_\_

Subscribed and sworn before me this

I hereby swear or affirm that the information given above is true and correct.

**28th** day of **May**, 19**45**Name **Elto Elto Chas****Mary L. Corbin** *Mary L. Corbin*

Notary Public

Position **Drig. & Prod. Foreman**Representing **The Texas Company**  
Company or OperatorMy commission expires **6-1-45**Address **Box 1270, Midland, Texas**

Remarks:

*Roy Yarbrough*  
Name \_\_\_\_\_  
Title \_\_\_\_\_

J.P. Reeves (continued)

10-sacks, leaving all the 13-3/8" casing cemented in the hole. The hole was filled with heavy mud between plugs and all mud and cement plugs were spotted by pumping in through drill pipe.