

**NEW MEXICO OIL CONSERVATION COMMISSION**  
**Santa Fe, New Mexico**

**MISCELLANEOUS REPORTS ON WELL**

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-offs, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below:

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL	XXXX		

PO Box #1231, Midland, Texas January 9, 1943  
 Place Date

OIL CONSERVATION COMMISSION,  
 Santa Fe, New Mexico

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the

Tide Water Associated Oil Co. Chas. S. Alves Well No. 1 in the  
 Company or Operator Lease  
SW/4 of NE/4 of Sec. 31 T. 18-S R. 35-E, N. M. P. M.,  
"Wildcat" Field, Lea County

The dates of this work were as follows: January 4-5-6 & 7, 1943.

Notice of intention to do the work was (was not) submitted on Form C-102 on Jan. 4, 19 43  
 and approval of the proposed plan was (was not) obtained. (Cross out incorrect words.)

**DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED**

The hole was filled to top with heavy mud, bridged, and a plug of 35 sacks of cement placed by the Halliburton pump method from 3247' to 3130'. Then the 8-5/8" casing was shot at approximately each 100' interval from 2510' to 759' and we recovered 759' of casing. The hole was bridged inside the 8-5/8" casing and cement plug of 25 sacks was placed from 1880' to 1838'. The top of the 13" OD surface casing was bridged and cemented with 15 sacks of cement. The regulation marker was erected.

Witnessed by E. W. Hogue Tide Water Associated Oil Co. Head Roustabout.  
 Name Company Title

**STATE OF TEXAS**  
**COUNTY OF MIDLAND**

Subscribed and sworn to before me this

12 day of January, 19 43

C. A. Clarke

My Commission expires 6-1-1943

I hereby swear or affirm that the information given above is true and correct.

Name Chas. Yarbrough  
 Position District Foreman  
Tide Water Associated Oil Company.  
 Representing Company or Operator

Address PO Box #1231, Midland, Texas.

Remarks:

Orig. & 2cc Con. Comm., Hobbs, NM.  
 cc Tulsa  
 Houston  
 Midland  
 Hobbs

Roy Yarbrough  
 Name  
 Title