

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. E-3496

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator AZTEC OIL & GAS COMPANY	8. Farm or Lease Name State AJ
3. Address of Operator P. O. Box 837, Hobbs, New Mexico 88240	9. Well No. 1
4. Location of Well UNIT LETTER M , 660 FEET FROM THE South LINE AND 660 FEET FROM THE West LINE, SECTION 1 TOWNSHIP 18-S RANGE 36-E NMPM.	10. Field and Pool, or Wildcat Arkansas Jct. - S.A.
15. Elevation (Show whether DF, RT, GR, etc.) 3795 GR	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

We propose to Plug & Abandon this well in the following manner:

1. Set 100' (25 sxs) cement plug from 5200-5100' (San Andres).
2. Load hole with 10# Mud Laden Fluid.
3. Set 100' (25 sxs) cement plug from 4080-3980' (Queen).
4. Set 100' (25 sxs) cement plug from 3147-3047' (Yates).
5. Set 100' (25 sxs) cement plug from 2057-1957' (Salt).
6. Set 100' (25 sxs) cement plug in and out of Surface Pipe.
7. Set 10 sxs cement plug at Surface with Dry Hole Marker, Clear & Level Location.
8. If Pipe is pulled, set 100' (25 sxs) cement plug in and out of Stub.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Nathan E. Olegg TITLE District Superintendent DATE Dec. 27, 1972

APPROVED BY Nathan E. Olegg TITLE OIL & GAS INSPECTOR DATE DEC 29 1972

CONDITIONS OF APPROVAL, IF ANY: