FORM C-105	NEW MEXICO OIL CONSERVATION COMMISSION
	Santa Fo, New Mexico
	WELL RECORD
	WELL RECORD
	Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?), SUBMIT IN TRIPLICATE, FORM C-110 WILL NOT BE APPROVED UNTIL
	Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE, FORM C-110 WILL NOT BE APPROVED UNTIL
AREA 640 ACRES LOCATE WELL CORRECTLY	FORM C-105 IS PROPERLY FILLED OUT.

Stanolind 011 an	d Cas Company	•	Por 2	Hobbs, N	ne Mexic	0	
	pany or Operator			Addı	ess		
Southeast Thousa	Well No.	in	ot	f Sec. 17	, 7	r <u>18</u>	
	M. P. M., 3119061		ield,		Lon		County.
Well is 550 feet s	outh of the North line an	<u>d 560</u>	_feet west of t	the East line of		17	······································
	gas lease is No		ssignment No.				
If patented land the own	er is	. <u> </u>		Address			
If Government land the	permittee is			, Address			
The Lessee is				, Address	·		
Drilling commenced	4-10	19_45	Drilling was co	mpleted	6-9		
Name of drilling contra	ctor Les Drilling	Janpany	, Addre	S8			
Elevation above sea leve	el at top of casing	51e	eet.				
	s to be kept confidential un		onfidentis	1	19		
	OI	L SANDS C	DR ZONES				
No. 1, from	to	I	No. 4, from		to	· · · · · · · · · · · · · · · · · · ·	
No. 2, from	to	]	No. 5, from	· · · · · · · · · · · · · · · · · · ·	to		
No. 3, from	to		No. 6, from		to		
	IMPO	RTANT W	ATER SANDS				
Include data on rate of	water inflow and elevation	n to which	water rose in l	hole.			
No. 1, from	to			feet	·		
No. 2, from	to			feet			
No. 3, from	to			feet	<u>,</u>		
No. 4, from	to			feet			
		CASING R	ECORD				

SIZE WÉIGHT PER FOOT KIND OF SHOE THREADS PER INCH CUT & FILLED FROM PERFORATED PURPOSE MAKE AMOUNT FROM то 13-3/8 9-5/8 1. L.Y. 43 292 3.8. None Burface String <u>z</u>, 3238 3 Neth. Mier. Salt string.

17 - <u>1</u>-1

My Commission expires

ŕ

.

## MUDDING AND CEMENTING RECORD

SIZE OF			NO. SACKS	1			· · · · · · · · · · · · · · · · · · ·	
HOLE	CASING	WHERE SE		METHOD US		UD GRAVITY	AMOUNT OF MUD USED	
17"	13-3/9	292	250	Halliburto	311			
12**	/8	3283						
		•						
<u> </u>	LI			PLUGS AND AI	)APTERS			
Heaving	plugM	aterial				Denth 5	Set	
							<u></u>	
-			RECORD OF SH					
SIZE	SHEL	USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT	
Results of	of shootin	g or chemic	al treatment					
•							·····	
			RECORD OF	DRILL-STEM	AND SPECIA	L TESTS		
If drill-s	tem or otl	ner special t	ests or deviation	surveys were m	nade, submit i	report on separat	e sheet and attach hereto.	
	Dri	11 Stes 2	fest Taken.	TOOLS US	ED ( and a	LIVIN I	· 10: 1	
Rotary t							feet tofeet	
							feet_tofeet	
				PRODUCT	ION			
Put to p	roducing_							
					rels of fluid o	of which	% was oil;%	
							- 	
If gas we	ell, cu, ft.	per 24 hour	S	Gal	lons gasoline	per 1,000 cu. ft.	of gas	
Rock pre	essure, lbs	. per sq. in.						
				EMPLOY	BES			
a ma	le Brya	at		Driller	<u>. 12</u> 13	inhinatt	, Driller	
Kan	roe Sat						, Driller	
				ION RECORD			, Dimor	
						te and correct re	ecord of the well and all	
work do	ne on it s	o lar as can	be determined fi	rom available r	ecoras.			
Subscrib	ed and sw	orn to befor	re me this 21	<b>Iİ</b>	lobbs.	les saries	<u></u>	
day of		***		14 45	Name ac	Replan	Date Date	
	32	~	. /			1		
<u> </u>	C. Tue)	<u>J</u>	Notary Public		Position	Field Super	1	
¢× ●	~~~~				Renresenting	Continue of Frank i		

Representing Stand Cil and Car Company Company or Operator

Address Now T, New Mexico

## FORMATION RECORD

FROM	τo	THICKNESS IN FEET	FORMATION
0 97 220 1927 2055 3010 3229 3803 4066 4122 4152 4152 4192 4559 4559 4559 4756 4847 4860	97 220 1927 2055 3010 3229 3803 4065 4122 4152 4192 4505 4522 4505 4522 4505 4502 4502 450	97	Caliche and water send Water sand Redbeds Anhydrite Salt and anhydrite Red beds and anhydrite Anhydrite Lime and gyp anhydrite Lime and gyp Lime Lime, anhydrite and gyp Lime and anhydrite Dolomite and anhydrite Anhydrite and lime Anhydrite and lime. Lime Lime Lime
1860	55 <b>22</b>		Lime.
	· ·	1. m <sup>. f. f.</sup>	
10TS: 5-10- 420'	5 DST 5420- rilling flu	528 9001 of	on 50 minutes. 5/8" choke -faint blow air recovered oil, water of gas. Flowing pressure 250. Shut-in
pre 381	re 13004.		The second
		n an	
-	۰ <u>-</u>		
	. 194		
· · · ·		la a sa A	
•			
-			
			a second s
	· · · · · ·		

. . . 

.....

· · · 

· · · · · ·

and the former that the . . . .