

Submit 3 Copies To Appropriate District

Office

District I

1625 N. French Dr., Hobbs, NM 88240

District II

811 South First, Artesia, NM 87210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-103

Revised March 25, 1999

WELL API NO. 30-125-3979 03979

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name:

State "RA"

8. Well No.

1

9. Pool name or Wildcat

San Andres Delaware

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

Oil Well ☐ Gas Well ☐ Other Disposal ☐

2. Name of Operator Yale E. Key Inc.

3. Address of Operator Box 2040 Hobbs, NM

4. Well Location

Unit Letter K : 1980 feet from the South line and 1909 feet from the West line

Section 31 Township 18S Range 36E NMPM County Lea

10. Elevation (Show whether DR, RKB, RT, GR, etc.)

3834 est

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

MIRU pulling unit

Release Baker lockset packer

POH laying down tubing

PU 2 7/8 work string RIH open ended to 4650'

Circulate hole w/10# salt gel mud consisting of at least 9.5# brine and 25# of gel/bbl.

Set cement plug from 4650'-4550' (1/2in 1/2out)

POH 1000' WOC 6-8 hrs.

RIH tag plug

POH set plug @ 1950'-1850'

POH set plug @ 400'-300' - TAG

Cut off wellhead ; spot 10sk plug @ surface; Install dry hole marker: Clean location

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Royce Crowell TITLE Compliance Specialist DATE 08/31/01

Type or print name Royce Crowell Telephone No. 393-9171

(This space for State use)

APPROVED BY TITLE DATE

Conditions of approval, if any:

910-4185

THE COMMISSION MUST BE NOTIFIED 24 HOURS PRIOR TO THE BEGINNING OF PLUGGING OPERATIONS FOR THE C-103 TO BE APPROVED.