



OIL CONSERVATION COMMISSION

SANTA FE, NEW MEXICO

RECEIVED

JUL - 3 1951

Miscellaneous Reports on Wells

OIL CONSERVATION COMMISSION
HOBBS OFFICE

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	X	REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			

July 3, 1951

Hobbs, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO.
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the
Stanolind Oil and Gas Company State **"W"** Well No. **1**

NE/4 Company or Operator **15** of Sec. **18-S** T. **37-E** R. **37-E**, N. M. P. M.,
Wildcat Field **Lea** County.

The dates of this work were as follows: **June 27 - 29, 1951**

Notice of intention to do the work was ~~(was not)~~ submitted on Form C-102 on **June 28** 19 **51**
and approval of the proposed plan was ~~(was not)~~ obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

At 8:00 A.M. on June 29, 1951, 48 hours after cementing the 9 5/8" casing at 4712' in two stages, the first stage was tested with 1000 PSI for 30 minutes before drilling the staging tool and Float Collar. No drop in pressure occurred. Float Collar and 46' of hard cement was drilled and shoe was tested with 1000 PSI for 30 minutes. No pressure drop occurred. Tests were considered satisfactory and drilling operations were resumed.

Witnessed by **C. R. Nichols** Name **Stanolind Oil and Gas Co.** Company **Prod. Foreman** Title

Subscribed and sworn before me this

3rd day of **July**, 19 **51**

[Signature]
Notary Public

My Commission Expires November 16, 1954

My commission expires

I hereby swear or affirm that the information given above is true and correct.

Name **Ralph H. Hunsicker**

Position **Field Superintendent**

Representing **Stanolind Oil and Gas Company**
Company or Operator

Address **Box F, Hobbs, New Mexico**

Remarks:

[Signature]
Oil & Gas Inspector
Title

APPROVED

JUL - 5 1951
Date

