

NE' MEXICO OIL CONSERVATION CON ISSION

SANTA FE, NEW MEXICO

MISCELLANEOUS NOTICES

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of notice by checking below:

OTICE OF INTENTION TO TEST CASING SHUT-OFF	x	NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL	
OTICE OF INTENTION TO CHANGE PLANS	-	NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING	
OTICE OF INTENTION TO REPAIR WELL	-	NOTICE OF INTENTION TO PLUG WELL	
OTICE OF INTENTION TO DEEPEN WELL	•		
Норр	s, New	Mexico June 28, 1951	
		Place Date	••••
IL CONSERVATION COMMISSION, anta Fe, New Mexico			
entlemen:			
ollowing is a notice of intention to do certain wor tanolind Oil and Gas Company St	rk as des Lato W	ribed below at the	
Company or Operator Le	250		
Sec. 15 , T. 18-S , R. 3 (-5	, 1	N. M. P. M. Wildcat	Fiel
Count	y.		
FULL DETAILS (OF PRO	POSED PLAN OF WORK	
DOLLOW MICHIGHICING IN MIN		AND REGULATIONS OF THE COMMISSION	
8:00 A. M. on June 29, 1951, 48 ho sing and cementing it in two stages it stage cemented with 600 sacks of mented second stage with 150 sacks	ours wi s at 47 8% Gel	11 have elapsed since running the 9 5/ 12'. DV staging tool set at 1665'. Cement and 100 sacks of Neat Cement. t cement. Top of Cement located at	3#
8:00 A. M. on June 29, 1951, 48 ho sing and cementing it in two stages at stage cemented with 600 sacks of	ours wi s at 47 8% Gel of nea ted wit	11 have elapsed since running the 9 5/ 12'. DV staging tool set at 1665'. Cement and 100 sacks of Neat Cement. t cement. Top of Cement located at	
8:00 A. M. on June 29, 1951, 18 ho using and cementing it in two stages at stage cemented with 600 sacks of mented second stage with 150 sacks 67' by temperature survey.	ours wi s at 47 8% Gel of nea ted wit	11 have elapsed since running the 9 5/ 12'. DV staging tool set at 1665'. Cement and 100 sacks of Neat Cement. t cement. Top of Cement located at	
8:00 A. M. on June 29, 1951, 18 ho using and cementing it in two stages at stage cemented with 600 sacks of mented second stage with 150 sacks 67' by temperature survey.	ours wi s at 47 8% Gel of nea ted wit	11 have elapsed since running the 95/ 12'. DV staging tool set at 1665'. Cement and 100 sacks of Neat Cement. t cement. Top of Cement located at h 1000 PSI before and after drilling drilling will be resumed.	and the second se
8:00 A. M. on June 29, 1951, 48 ho using and cementing it in two stages at stage cemented with 600 sacks of mented second stage with 150 sacks 67' by temperature survey. It the above time casing will be test ach stage, and if tests are satisfac	ours wi s at 47 8% Gel of nea ted wit	11 have elapsed since running the 9 5/ 12'. DV staging tool set at 1665'. Cement and 100 sacks of Neat Cement. t cement. Top of Cement located at	and the second se
pproved	ours wi s at 47 8% Gel of nea ted wit	11 have elapsed since running the 95/ 12'. DV staging tool set at 1665'. Cement and 100 sacks of Neat Cement. t cement. Top of Cement located at h 1000 PSI before and after drilling drilling will be resumed. UL-2 PSI UL-2 PSI PSI PSI PSI PSI PSI PSI PSI	and the second se
pproved	ours wi s at 47 8% Gel of nea ted wit	11 have elapsed since running the 95/ 12'. DV staging tool set at 1665'. Cement and 100 sacks of Neat Cement. t cement. Top of Cement located at h 1000 PSI before and after drilling drilling will be resumed. UUL - 2 Mod UUL - 2 Mod	and the second se
pproved	ours wi s at 47 8% Gel of nea ted wit	11 have elapsed since running the 95/ 12'. DV staging tool set at 1665'. Cement and 100 sacks of Neat Cement. t cement. Top of Cement located at h 1000 PSI before and after drilling drilling will be resumed. UL-2 PSI UL-2 PSI PSI PSI PSI PSI PSI PSI PSI	
pproved	ours wi s at 47 8% Gel of nea ted wit	11 have elapsed since running the 95/ 12'. DV staging tool set at 1665'. Cement and 100 sacks of Neat Cement. t cement. Top of Cement located at h 1000 PSI before and after drilling drilling will be resumed. UL-2 PSI UL-2 PSI PSI PSI PSI PSI PSI PSI PSI	