

## NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELL

Submit this report in triplicate to the Oil Conservation Commission or its proper agent **ten days** after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-offs, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below:

|  |  |  |          |
|--|--|--|----------|
| REPORT ON BEGINNING DRILLING OPERATIONS                    |  | REPORT ON REPAIRING WELL                       |          |
| REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL |  | REPORT ON PULLING OR OTHERWISE ALTERING CASING |          |
| REPORT ON RESULT OF TEST OF CASING SHUT-OFF                |  | REPORT ON DEEPENING WELL                       | <b>X</b> |
| REPORT ON RESULT OF PLUGGING OF WELL                       |  |  |          |

Monument New, Mexico

October 29, 1941

OIL CONSERVATION COMMISSION,  
Santa Fe, New Mexico.

Place

Date

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the

**Amerada Petroleum Corporation** State **N** Well No. **1** in the  
**SW NW** Company or Operator **24** Lease **18**  
**Hobbs** of Sec. **24**, T. **18**, R. **37**, N. M. P. M.,  
Field. **9-13-41 to 10-28-41** County

The dates of this work were as follows:

Notice of intention to do the work was (was not) submitted on Form C-102 on \_\_\_\_\_ 19\_\_\_\_  
and approval of the proposed plan was (was not) obtained. (Cross out incorrect words)

**DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED**  
D.4240' deepen to 4319' and set liner of 237' 5 1/2" 14# Smls casing liner @ 4249'.  
plugged back from 4319' to 4241' w/ 16 sacks stardor cement, and perforated 5 1/2" casing w/ lane wells 66 shots from 4212' to 4234' (No results) Set 5 1/2" Baker Cement retainer @ 4206' w/ 25 sacks starcor cement perforated 5 1/2" casing w/ lane wells 42 shots 4192' to 4206' and w/ 30 shots from 4140' to 4150' and set 5 1/2" x 2 1/2" EUE Lane wells hook wall packer, swabbed well no results.

Witnessed by \_\_\_\_\_ Name \_\_\_\_\_ Company \_\_\_\_\_ Title \_\_\_\_\_

Subscribed and sworn to before me this **29** day of **October**, 19**41**

I hereby swear or affirm that the information given above is true and correct.

Name **Do. Topp**Position **Ass't Supt**Representing **Amerada Pet. Corp.**

Company or Operator

Address **Monument N.M.**My Commission expires **2-21-44**

Remarks:

**Roy Garbros**  
Name  
**OIL & GAS INSPE**  
Title

