

DUPLICATE **OIL CONSERVATION COMMISSION** **Santa Fe, New Mexico** **MISCELLANEOUS REPORTS ON WELLS**

RECEIVED
AUG 14 1946
RECEIVED

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within the time specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below:

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL		REPORT ON DEEPENING WELL	X

Monument, New Mexico.
 Place

August 12, 1946
 Date

OIL CONSERVATION COMMISSION,
 SANTA FE, NEW MEXICO.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the

Amerada Petroleum Corporation State E Well No. 2 in the
 Company or Operator Lease

N. M. P. M. of NW 24 of Sec. 24, T. 18S, R. 37E, N. M. P. M.,
Hobbs Field, Lea County.

The dates of this work were as follows: August 8th to

Notice of intention to do the work was (~~submitted~~) submitted on Form C-102 on August 4, 19 46
 and approval of the proposed plan was (~~obtained~~) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

4262' Drilled out depth, Gun perforated with Lane Wells from 4230 to 4232 with 12 holes. Ran Baker Retrievable Cement Retainer on 2" EUE and set at 4130' and tested below with 3500# Pressure and above Retainer with 1000# for 30 Minutes and was OK. Gun Perforated with Lane Wells with 4 Shots per foot from 4234' to 4262', Total of 112 shots, layed down drill pipe and started in hole with 3" EUE Tubing, 5 1/2" x 2" EUE Type G American Control Head Packer, Tubing set at 4259' and Packer set at 4186', with perforations below and swabbed for 20 hours and swabbed 90 Bbls of fluid, which was 8 bbls of oil and 82 bbls water, Pulling tubing and will plug back with Dowell Plastic.

Witnessed by D. F. Furse Name Amerada Pet. Corp. Foreman
 Company Title

Subscribed and sworn before me this

I hereby swear or affirm that the information given above is true and correct.

12 day of August, 19 46

Name Walter James

Position Farm Boss.

Representing Amerada Pet. Corp.,
 Company or Operator

My commission expires My Commission Expires May 9, 1948

Address Drawer D, Monument, New Mexico.

Remarks:

APPROVED

Date AUG 14 1946

Roy Yushrough
 Name
Oil & Gas Inspector
 Title

