

NEW MEXICO OIL CONSERVATION COMMISSION  
Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF	<input checked="" type="checkbox"/>	REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL		REPORT ON RECOMPLETION OPERATION		REPORT ON (Other)	

March 25, 1955  
(Date)

Hobbs, New Mexico  
(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Humble Oil & Refining Company  
(Company or Operator)

New Mexico State A  
(Lease)

Cackle Drilling Company  
(Contractor)

Well No. 7 in the SE 1/4 SE 1/4 of Sec. 25

T. 18S, R. 37E, NMPM, Hobbs Pool, Lea County.

The Dates of this work were as follows: 3-22 to 3-24-55

Notice of intention to do the work (was) ~~waived~~ submitted on Form C-102 on February 21, 1955,  
(Cross out incorrect words)

and approval of the proposed plan (was) ~~waived~~ obtained.

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Run 100 joints 5-1/2-inch casing, 4175.41 feet set at 4187.01 feet. Cemented with 100 sacks regular neat cement. Plug on bottom at 8:00 P.M., 3-22-55. Three centralizers at 4181, 4141, and 4100 feet. Run temperature survey after 6 hours and found top of cement at 3682 feet. Perforated casing with 2 one-half-inch holes and recemented with 1250 sacks regular cement with 12% gel and 100 sacks regular neat cement. Plug in place at 7:00 A.M., 3-23-55. Circulated approximately 200 sacks. Cement slurry 12.4#.

Tested casing with 1900# GWP for 30 minutes. Test O.K. No drop in pressure. Perforated from 4146 to 4187 feet and stuck gun. Now preparing to fish perforating gun.

The elevation of this well is 3654 ground level.

Witnessed by *J. E. Rojice*  
(Name)

Humble Oil & Refining Company  
(Company)

Tool Pusher  
(Title)

Approved: OIL CONSERVATION COMMISSION

*J. Stanley*  
(Name)

(Title)

(Date)

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name

Position District Superintendent

Representing Humble Oil & Refining Company

Address Box 2347, Hobbs, New Mexico