NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico



MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

	of the Commission. Indicate Nature of Report by Checking	ng Belov	w	
REPORT ON BEGINNING DRILLING OPERATIONS	REPORT ON RESULT OF TEST OF CASING SHUT-OFF	X	REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL	REPORT ON RECOMPLETION OPERATION		REPORT ON (Other)	
			Hebbs, New Mex	Loo ace)
Following is a report on the work d	done and the results obtained under tne hea	ding not	ed above at the	
Kumble Uil & Mafining Company or Opers	apany	Mari	Mexico State A	••••••
	, Well No	7	•	f Sec 25
	Hebbs Pool			
The Dates of this work were as follows:	2-28, 3-1-55			
Notice of intention to do the work (was)	submitted on Form C-102 on	(C	cross out incorrect words)	19
d 1 of the managed mlam (suppl)				
and approval of the proposed plan (was)	(traped) obtained.			
DETAIL	ED ACCOUNT OF WORK DONE AND I			
Han 11 joints 8-5/8-inch Greented with 225 sacks 43 weight 14.4 and 14.8%. Ci	ED ACCOUNT OF WORK DONE AND I D 24 3-55 casing, total of s gel cement. Plug on bottom ironiated approximately 50 so CMP for 30 minutes. Test U.S.	331.1 : at 2 : oks.	6 feet set at 344.22 2:50 r.m., 2-23-55.	Slurry
Han 11 joints 8-5/8-inch (consuted with 225 sacks 43 weight 14.4 and 14.8%. City Tested casing with 1000% (ED ACCOUNT OF WORK DONE AND I D 24 3-55 casing, total of s gel cement. Plug on bottom ironiated approximately 50 so CMP for 30 minutes. Test U.S.	331.1 : at 2 : oks.	6 feet set at 344.22 2:50 r.m., 2-23-55.	Slurry
Ran 11 joints 8-5/8-inch 6 cemented with 225 sacks 43 weight 14.4 and 14.8%. Citested casing with 1000% 6 plug at 3:00 P.M., 3-1-55.	ED ACCOUNT OF WORK DONE AND I D 24 3-55 casing, total of s gel cement. Plug on bottom ironiated approximately 50 so CMP for 30 minutes. Test U.S.	331.1 : at 2 : oks.	6 feet set at 344.22 2:50 r.m., 2-23-55.	Slurry
Ran 11 joints 8-5/8-inch 6 cemented with 225 sacks 43 weight 14.4 and 14.8%. Citested casing with 1000% 6 plug at 3:00 P.M., 3-1-55.	ED ACCOUNT OF WORK DONE AND I D 24 3-55 casing, total of s gel cement. Plug on bottom ironiated approximately 50 so CMP for 30 minutes. Test U.S.	331.1 : at 2 : oks.	6 feet set at 344.22 2:50 r.m., 2-23-55.	Slurry
Ran 11 joints 8-5/8-inch Greented with 225 sacks 43 weight 14.4 and 14.8%. Give Tested casing with 1000% Gplug at 3:00 P.M., 3-1-55.	ED ACCOUNT OF WORK DONE AND I D 24 3-55 casing, total of s gel cement. Plug on bottom ironiated approximately 50 so CMP for 30 minutes. Test U.S.	331.1 at 2 loks.	6 feet set at 344.22 2:50 r.m., 2-23-55.	Slurry
Ran 11 joints 8-5/8-inch Greented with 225 sacks 43 weight 14.4 and 14.8%. Givented casing with 1000% Gipling at 3:00 P.M., 3-1-55. Now drilling.	ED ACCOUNT OF WORK DONE AND I 24 3-55 casing, total of is gel cement. Plug on bottom irenlated approximately 50 sel WP for 30 minutes. Test U.F. (Company) I hereby cert	331.1 at 2 loks. No	is feet set at 344.22 2:50 P.M., 2-23-55. Top in pressure. The Land Pusher (Title)	Slurry
Ran 11 joints 8-5/8-inch Comented with 225 sacks 43 weight 14.4 and 14.8%. Cit Tested casing with 1600% Ciplug at 3:00 r.m., 3-1-55. Now drilling.	ED ACCOUNT OF WORK DONE AND I DE 24 4-55 casing, total of a gel coment. Plug on bottom ironiated approximately 50 seller for 30 minutes. Test U.F. CMP for 30 minutes. Test U.F. Company I hereby cert to the best of the period of th	331.1 at 2 locks. Note that if the that if my known we have the that if the that it is not the the the that it is not the the the the the the the the the th	is feet set at 344.22 2:50 P.M., 2-23-55. Top in pressure. The Land Pusher (Title)	Slurry
Ran 11 joints 8-5/8-inch Comented with 225 sacks 43 weight 14.4 and 14.8%. Cit Tested casing with 1600% Ciplug at 3:00 r.m., 3-1-55. Now drilling.	ED ACCOUNT OF WORK DONE AND I 24 3-55 casing, total of included approximately 50 sections. Test U.R. Disconnection of the control of the co	331.1 at 2 loks. No	the information given above is true	orilled

jmb