

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS NOTICES

RECEIVED
JAN 26 1954

Submit this notice in **TRIPLICATE** to the District Office, Oil Conservation Commission, before the work is started. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection of the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL	X	NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Hobbs, New Mexico

January 22, 1954

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

Makin Drilling Co. (Charles P. Miller, Agent) Well No. **1** in **H** (Unit)
(Company or Operator)
88 1/4 **88** 1/4 of Sec. **29**, T. **18S**, R. **37E**, NMPM., **Wildcat** Pool
(40-acre Subdivision)
Lee County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

We propose to plug and abandon #1 McMillan at a total depth of 5797'. No shows of oil or gas have been encountered. A drill stem test from 3820' to 3882'; tool open 1 hour; recovered 160' of drilling mud. A drill stem test from 4469' to 4640'; tool open 35 minutes; recovered 1650' of salt water. A drill stem test from 5574' to 5640'; tool open 45 minutes; recovered 4075' of sulphur water and 200' of drilling mud. Samples indicate the presence of sulphur water at the bottom of hole.

In line with verbal approval we propose to plug the well as follows: We will set a 25 sack cement plug at 5574'; another 25 sack plug at 4469'; and still another 25 sack plug at 1529' in the bottom of the 8-5/8" casing. We will leave the hole filled with heavy rotary mud and will set a regulation marker in the surface casing when derrick is moved from location. We will back fill, and level all pits and leave the surface in as nearly the condition found as is possible.

Approved....., 19.....
Except as follows:

Company or Operator

By.....

Position.....
Send Communications regarding well to:

Approved
OIL CONSERVATION COMMISSION

By.....

Oil & Gas Inspector

Title.....

Name..... **Charles P. Miller**

Address..... **Box 385, Hobbs, N.M.**