

| | |
|------------------------|--|
| NO. OF COPIES RECEIVED | |
| DISTRIBUTION | |
| SANTA FE | |
| FILE | |
| U.S.G.S. | |
| LAND OFFICE | |
| OPERATOR | |

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

| | |
|--------------------------------|---|
| 5a. Indicate Type of Lease | |
| State <input type="checkbox"/> | Fee <input checked="" type="checkbox"/> |
| 5. State Oil & Gas Lease No. | |

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

| | |
|---|--|
| 1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <input type="checkbox"/> | 7. Unit Agreement Name |
| 2. Name of Operator M. Brad Bennett, Inc. | 8. Farm or Lease Name Goodwin "30" |
| 3. Address of Operator P.O. Box 2062 Midland, Texas 79702 | 9. Well No. h |
| 4. Location of Well UNIT LETTER E, 660 FEET FROM THE West LINE AND 1980 FEET FROM THE North LINE, SECTION 30 TOWNSHIP 18-S RANGE 37-E NMPM. | 10. Field and Pool, or Wildcat Goodwin (Drinkard) |
| 15. Elevation (Show whether DF, RT, CR, etc.) | 12. County Lea |

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☒
CHANGE PLANS ☐
OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOBS ☐
OTHER ☐
ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1. Plan to MIRU 6/1/88 POOH w/ tubing and rods.
2. Cut and pull 5 1/2" @ approx. 6500', spot 15 sx. inside 5 1/2" stub and 20 sx. outside stub in open hole. Estimate plug 6450-6550'. W.O.C. and tag plug.
3. Spot 80 sx. from 4518-4718'.
4. Spot 35 sx. from 3346-3246' to isolate 8 5/8" shoe @ 3296'.
5. Cut and pull 9 5/8" casing at approx. 2600'. Spot 20 sx. inside 9 5/8" stub and 35 sx. outside stub in open hole. Estimate plug 2650-2550'. W.O.C. and tag plug.
6. Spot 70 sx. plug from 406-306' to isolate 13 3/8" shoe at 356'.
7. Spot 10 sx. plug at surface, cut off wellhead and install P&A marker.
8. Sketch attached.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

M. Brad Bennett

SIGNED M. Brad Bennett TITLE President-M. Brad Bennett, Inc. DATE May 18, 1988

ORIGINAL SIGNED BY JERRY SEXTON
SUPERVISOR

APPROVED BY _____ TITLE _____ DATE MAY 20 1988

CONDITIONS OF APPROVAL, IF ANY:

17 1/2" hole

12 1/4" hole

Red Bed 0-1500'
Mudstone 1550-1700'
Silt 1700-2730'
Mud, sh. sl. 2750-3200'

T. Yates 2875'
San Andres 4568'
Clench 6871'

Perf. 7000-7099

Perf 7296-7340
Perf 7347-7358
Perf 7377-7392
Perf 7416-7432

Perfs 7446-7462
CIBP@7500

5R 75 SX.

Cem 6800' Temp survey

CIBP@7225' C.I.C 4 SX.

PBTD 7428'

Cement Retainer

(175 ft) 14# J-55
5 1/2" (96 ft) 17# N-80 @7554'
Cem w/150 SX.
Cem top 6800' Temp Survey.
Set w/110,000 # tension on slips

(13 ft) 13 3/8" 48# H-40 @356'
Cem w/375 SX. Circ.

Cem @2800' Temp Survey.
(107 ft) 9 5/8" 36# H-40 & J-55 @3296'
Cem w/175 SX.
Cem top 2800' temp survey.

8 3/4" hole