



STATE LAND OFFICE
SANTA FE, NEW MEXICO

J. F. HINKLE
COMMISSIONER OF PUBLIC LANDS

SHEET NO. 2

<u>From</u>	<u>To</u>	<u>Formation</u>
3775	3795	Brown Lime
3795	3805	Gray Lime
3805	3840	Brown Lime
3840	3845	Hard Sand SHOW GAS 3845
3845	3855	Lime (Fine and Hard)
3855	3860	Shale ESTIMATED 10 MI. GAS AT 3860
3860	3866	Broken Lime and Sand
3866	3880	Lime
3880	3900	Hard Lime SHOW GAS AT 3881
3900	3940	Lime
3940	3980	Hard Lime
3980	4030	Sandy Lime
4030	4060	Hard Lime
4060	4074	Medium Lime
4074	4077	Hard Lime
4077	4090	Medium Lime
4090	4094	Hard Lime SHOW OIL AND GAS
4094	4100	Medium Lime
4100	4152	Soft Lime
4152	4155	Sandy Lime SLIGHT OIL AND GAS SHOW
4155	4188	Soft Lime
4188	4195	Hard Lime
4195	4230	Soft Lime INCREASE IN OIL AND GAS AT 4215
4230	4255	Medium Lime A LITTLE WATER AT 4230
4255	4272	Limes SULPHUR WATER AT 4265

NOTE: Hole plugged to 4188'.

Casing Record: 15-1/2" - 240' Cemented 75 sax
10" - 1651' Cemented ? sax
8-5/8" - 3878' Cemented 75 sax

Set whip stock at 3760'. Tested water shut-off on February 26, 1931.
Gas Puff 2995', Show gas 3040', Show gas 3060', Light oil show 3315',
Oil and water 3620', Gas and oil show 3760', Gas 3845', Increase gas
3860' estimated from 4 to 16 Mi..