

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

NEW MEXICO OIL CONSERVATION COMMISSION

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Amerada Hess Corporation	8. Farm or Lease Name State "C"
3. Address of Operator Drawer D, Monument, New Mexico 88265	9. Well No. 1
4. Location of Well UNIT LETTER <u>A</u> <u>330</u> FEET FROM THE <u>North</u> LINE AND <u>330</u> FEET FROM THE <u>East</u> LINE, SECTION <u>36</u> TOWNSHIP <u>18-S</u> RANGE <u>37-E</u> NMPM.	10. Field and Pool, or Wildcat Hobbs
15. Elevation (Show whether DF, RT, GR, etc.) 3659' DF	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:
REMEDIAL WORK ☒
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOBS ☐
OTHER ☐
ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

March 1977:

Pumped 500 gal. Xylene down csg. Pulled rods, pump and 2-7/8" tbg. Ran 4-1/2" sand pump. Ran 3-1/2" sand pump. Attempted to recover fish from open hole. No results. Ran pkr. on 2-7/8" tbg., set pkr. at 3986'. Acidized Grayburg San Andres zone in open hole fr. 4062' to 4167' with 500 gal. Xylene, 1000 gal. 2% KCl water, 7500 gal. 20% NE acid. Flushed with 30 bbls. 2% KCl water. Swabbed back load. Pulled tbg. & pkr. Ran 2-7/8" tbg. set at 4088', S.N. at 4084' & tbg. anchor catcher at 3926'. Ran 2-1/2" x 1-1/4" x 8' x 12' RHBC pump on rods and resumed pumping.

Test of 3-25-77: Pumped 33 b.o. & 99 b.w. in 24 hrs. on 8-48" SPM?

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>E. B. Sexton</u>	TITLE <u>Supv. Adm. Ser.</u>	DATE <u>3-28-77</u>
SIGNED by <u>Jerry Sexton</u>		
APPROVED BY <u>Dist 1, Supv.</u>	TITLE <u></u>	DATE <u>MAR 31 1977</u>
CONDITIONS OF APPROVAL, IF ANY:		

RECEIVED

MAR 30 1977

OIL CONSERVATION COMM.
HOBBS, N. M.