

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.O.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-7

5a. Indicate Type of Lease
State ☒ Fee ☐
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT - 1" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name N. HOBBS (G/SA) UNIT
2. Name of Operator SHELL OIL COMPANY	8. Farm or Lease Name SECTION 24
3. Address of Operator P. O. BOX 991, HOUSTON, TX 77001	9. Well No. 211
4. Location of Well UNIT LETTER C 660 FEET FROM THE NORTH LINE AND 1980 FEET FROM THE WEST LINE, SECTION 24 TOWNSHIP 18-S RANGE 37-E NMPM.	10. Field and Pool, or Wildcat HOBBS (G/SA)
15. Elevation (Show whether DF, RT, GR, etc.) 3675' DF	12. County LEA

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input checked="" type="checkbox"/> *	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

9-08-82: Set RBP @ 4073' in 5" liner. Press tested csg to 700 psi for 15 mins - held OK.
Spotted 2 sx of sand on RBP.
9-09-82: Shot 4 squeeze holes @ 2700'. Set cmt retainer @ 2599'. Mixed and pumped 2000 sx HOWCO LITE cmt plus 8#/sx salt and 500 sx Class "C" cmt. Mixed and pumped 300 sx Class "C" cmt and squeezed into formation. WOC.
9-11-82 to 9-13-82: Drld cmt and cmt retainer 2585' to 2760'. Press tested squeeze holes @ 2700' to 700 psi for 10 mins - held OK.
9-14-82: Retrieved BP, installed production equipment and returned well to production.

* PER NEW MEXICO OIL CONSERVATION DIVISION REQUEST.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Eddie W. Seay A. J. FORE TITLE SUPERVISOR REG. & PERMITTING DATE JANUARY 25, 1982

APPROVED BY ORIGINAL SIGNED BY EDDIE W. SEAY TITLE DATE JAN 28 1983

RECEIVED

JAN 27 1983

**C.C.D. ... 120
HOBBS OFFICE**