

COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. Unit Agreement Name
2. Name of Operator Amerada Hess Corporation		8. Farm or Lease Name H. D. McKinley
3. Address of Operator Drawer D, Monument, New Mexico 88265		9. Well No. 1
4. Location of Well UNIT LETTER <u>D</u> <u>330</u> FEET FROM THE <u>North</u> LINE AND <u>330</u> FEET FROM THE <u>West</u> LINE, SECTION <u>30</u> TOWNSHIP <u>18-S</u> RANGE <u>38-E</u> N.M.P.M.		10. Field and Pool, or Wildcat Hobbs Grayburg San Andres
15. Elevation (Show whether DF, RT, GR, etc.) 3650' GR		12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input checked="" type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

April and May 1977

Pulled rods, pump and tbgs. Ran gamma ray, caliper, compensated neutron and density logs. Set 4-1/2" OD 10.5# K-55 hydril flush joint liner from 3784' to 4229' and cemented with 70 sks. Class C cement with additives. Cemented top of liner with 150 sks. Class C cement with additives. Drld. out cement inside 7" csg. and 4-1/2" liner & tested OK. Ran cement bond log, gamma ray and collar locator. Perf. 4-1/2" liner opposite Grayburg San Andres zone from 4120' to 4128', 4138' to 4150', 4154' to 4158' & fr. 4161' to 4168' with 2 SPF. Re-ran tbgs., pump and rods and resumed production.

Test prior to work: 1-6-77: Pumped 41 b.o. & 175 b.w. in 24 hrs. on 16-64" SPM.
Test after work: 5-18-77: Pumped 80 b.o. & 213 b.w. in 24 hrs. on 16-64" SPM.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED E. S. Fisher TITLE Supv. Adm. Ser. DATE 5-18-77

APPROVED BY _____ TITLE _____ DATE 1977

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

MAY 16 1977

U.S. CONSERVATION COMM.
HOBBES, N. H.