



NEW MEXICO OIL CONSERVATION COMMISSION  
Santa Fe, New Mexico

WELL RECORD

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPLICATE. If State Land submit 6 Copies

AREA 640 ACRES  
LOCATE WELL CORRECTLY

O. D. Alsabrook  
(Company or Operator)

Saunders  
(Lease)

Well No. J-1, in NW 1/4 of S.E. 1/4, of Sec. 3, T. 18S, R. 38E, NMPM.  
Undesignated Pool, Lea County.

Well is 1980 feet from South line and 1980 feet from East line  
of Section 3. If State Land the Oil and Gas Lease No. is

Drilling Commenced 4-25, 1958. Drilling was Completed 5-14, 1958.

Name of Drilling Contractor Howard P. Holmes Drilling Contractor

Address Hobbs, New Mexico

Elevation above sea level at Top of Tubing Head 3649.2' G. L. The information given is to be kept confidential until , 19

OIL SANDS OR ZONES

No. 1, from 4104 to 4140 No. 4, from to  
No. 2, from 4914 to 5196 No. 5, from to  
No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet.  
No. 2, from to feet.  
No. 3, from to feet.  
No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
8 5/8	24	New	324	Texas P.	None	-	Surface

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. BAGS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
12 1/4	8 5/8	324	200	Halliburton		

RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

None

Result of Production Stimulation

Depth Cleaned Out

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from 0 feet to 5196 feet, and from feet to feet.  
Cable tools were used from feet to feet, and from feet to feet.

PRODUCTION

Put to Producing None, 19

OIL WELL: The production during the first 24 hours was None barrels of liquid of which % was  
was oil; % was emulsion; % water; and % was sediment. A.P.I.  
Gravity.

GAS WELL: The production during the first 24 hours was None M.C.F. plus barrels of  
liquid Hydrocarbon. Shut in Pressure lbs.

Length of Time Shut in.

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy.....1962'	T. Devonian.....	T. Ojo Alamo.....	
T. Salt.....	T. Silurian.....	T. Kirtland-Fruitland.....	
B. Salt.....	T. Montoya.....	T. Farmington.....	
T. Yates.....3232'	T. Simpson.....	T. Pictured Cliffs.....	
T. 7 Rivers.....	T. McKee.....	T. Menefee.....	
T. Queen.....1104'	T. Ellenburger.....	T. Point Lookout.....	
T. Grayburg.....	T. Gr. Wash.....	T. Mancos.....	
T. San Andres.....4914'	T. Granite.....	T. Dakota.....	
T. Glorieta.....	T. ....	T. Morrison.....	
T. Drinkard.....	T. ....	T. Penn.....	
T. Tubbs.....	T. ....	T. ....	
T. Abo.....	T. ....	T. ....	
T. Penn.....	T. ....	T. ....	
T. Miss.....	T. ....	T. ....	

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	1952	1952	Surface & Red Bed				
1952	2350	398	Anhydrite				
2350	3037	687	Anhydrite & Salt				
3037	3562	525	Anhydrite & Gyp				
3562	3889	327	Anhydrite & Lime				
3889	4914	1025	Anhydrite & Lime & Shale				
4914	5196	282	Lime T. D.				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Company or Operator. O. D. Alsabrook Address. Box 667, Hobbs, New Mexico  
Name. Howard P. Holmes Title. Agent

O. D. Alsabrook "J" Well No. 1, in NW 1/4 of SE 1/4 of Sec. 3,  
T18S, R38E, Lea County, New Mexico.

D.S.T. #1

Halliburton Test Tool - 5/8" B. H. Ch.  
Test 4840' - 4907' open 1 hr. 20 mins.  
Recover 60' mud.  
I.F. 30# F.F. 30# - 30 min B.H.P.S.I. 360#

D.S.T. #2

Halliburton Straddle Packer Test.  
5/8" B. Ch. - Test 4117' to 4084'.  
Tool open 1 hr. 30 mins.  
Recover 30' Slightly oil & gas cut mud.  
100' mud.  
I.F. 68# F.F. 80# B.H.P.S.I. 30 mins. 385#.  
Hydrostatic mud wt. 2285#.