

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL	XX	NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Hobbs, New Mexico
(Place)

June 21, 1957
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

Sinclair Oil & Gas Company - Pearl Forest (Company or Operator) Well No. 1 in H (Unit)
SE 1/4 NE 1/4 of Sec. 11, T. 10S, R. 30E, NMPM, Undesignated Pool
LaSalle County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

TD 4200'

Set 7"OD Casing @ 4200' w/ 100 Sk. on Bottom & 100 Sk. Thru 2-stage tool @ 1914'
Perforated Casing f/ 4004-96; 4108-12 w/ 64 Jet holes
Acidized Perforations w/ 500 Gal. mud acid & Fractured w/ 20,000 Gal. & 20,000# Sand
Swabbed dry
Perforated Casing f/ 4170 to 4180 w/ 40 jet holes
Fractured w/ 10,000 Gal. oil & 10,000# Sand - Swabbed dry-
Top Cement behind 7"OD Casing @ 1190' from surface
Propose to 25 Sk. Cement Plug in bottom to cover all Perforations
Fill hole with heavy mud- Shoot off 7"OD Casing @ 1190' annular
Set 15 Sk. cement plug in bottom of 10 3/4"OD Casing set @ 306 Ft.
Fill hole with heavy mud to bottom of cellar top of 10 3/4" Casing-
Set Regulation Marker 4" Extending 4' above surface level, in 10 Sk. cement in
to of 10 3/4" Casing & Bottom of cellar- Completed Plug & Abandon.

Approved....., 19.....
Except as follows:

Spot 10 sack plug in and out of
top of 7"OD

Approved
OIL CONSERVATION COMMISSION

By.....
Title.....

Sinclair Oil & Gas Company
Company or Operator

By.....

Position..... Dist. Supt.

Send Communications regarding well to:

Name..... C. C. Salter, 520 E. Broadway, Hobbs, N.M.

Address.....