



NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPLICATE. If State Land submit 6 Copies

AREA 640 ACRES
LOCATE WELL CORRECTLY

W. R. WEAVER

(Company or Operator)

Mrs. Charlcia A. Taylor

(Lease)

Well No. 2, in NW $\frac{1}{4}$ of SE $\frac{1}{4}$, of Sec. 11, T. 18-S, R. 38-E, NMPM.

Bishop Canyon - Queen

Pool,

Lea

County.

Well is 1980 feet from East line and 1980 feet from South line

of Section 11. If State Land the Oil and Gas Lease No. is

Drilling Commenced July 7th, 1957 Drilling was Completed July 23rd, 1957

Name of Drilling Contractor Forster Drilling Company

Address P. O. Box 588 - Odessa, Texas

Elevation above sea level at Top of Tubing Head 3632.95 (Ground Level) The information given is to be kept confidential until March 26th, 1958

OIL SANDS OR ZONES

No. 1, from 4107 to 4118 No. 4, from to

No. 2, from to No. 5, from to

No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from 125 to 70 feet.

No. 2, from to feet.

No. 3, from to feet.

No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
8-5/8"	24#	New	330.24	Larkin	None	None	- - - -
5-1/2"	15.50#	New	4151.41	Baker	2692.95	4107 - 4118	To Produce

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
12-1/4"	8-5/8"	342.92	200	Pump	- - -	Cemented to Top
7-7/8"	5-1/2"	4164.41	400	Pump	44	Top Cement 2740

RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

Well given frac treatment of 10,000 gallons of oil and 10,000 pounds of sand thru perforations at 4107 to 4118'

Result of Production Stimulation Well flowed 100% Salt Water -- Plugged and Abandoned

Depth Cleaned Out

JORD OF DRILL-STEM AND SPECIAL TE

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from 0' feet to 4165' TD feet, and from _____ feet to _____ feet.
 Cable tools were used from _____ feet to _____ feet, and from _____ feet to _____ feet.

PRODUCTION

Put to Producing **"Plugged & Abandoned"**, 19____.

OIL WELL: The production during the first 24 hours was _____ barrels of liquid of which None % was
 was oil; _____ % was emulsion; 100 % water; and _____ % was sediment. A.P.I.
 Gravity _____.

GAS WELL: The production during the first 24 hours was _____ M.C.F. plus _____ barrels of
 liquid Hydrocarbon. Shut in Pressure _____ lbs.

Length of Time Shut in _____.

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico

Northwestern New Mexico

T. Anhy. _____	T. Devonian _____	T. Ojo Alamo _____
T. Salt _____	T. Silurian _____	T. Kirtland-Fruitland _____
B. Salt _____	T. Montoya _____	T. Farmington _____
T. Yates <u>3263</u>	T. Simpson _____	T. Pictured Cliffs _____
T. 7 Rivers _____	T. McKee _____	T. Menefee _____
T. Queen <u>4106</u>	T. Ellenburger _____	T. Point Lookout _____
T. Grayburg _____	T. Gr. Wash _____	T. Mancos _____
T. San Andres _____	T. Granite _____	T. Dakota _____
T. Glorieta _____	T. <u>Rustler 2015</u>	T. Morrison _____
T. Drinkard _____	T. _____	T. Penn _____
T. Tubbs _____	T. _____	T. _____
T. Abo _____	T. _____	T. _____
T. Penn _____	T. _____	T. _____
T. Miss _____	T. _____	T. _____

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	333	333	Red Bed and Shells				
333	2031	1698	Red Bed				
2031	2062	31	Anhydrite				
2062	2110	48	Anhydrite & Red Bed				
2110	3283	1173	Anhydrite & Salt				
3283	3630	347	Anhydrite & Gyp				
3630	3930	300	Anhydrite, Gyp & Lime				
3930	4022	92	Gyp and Lime				
4022	4095	73	Lime				
4095	4142	47	Diamond Core:				
			Anhydrite, red shale &				
			dolomitic sandstone				
4142	4165	23	Drilled to Total Depth				
			Lime and Sand				
			"PLUGGED AND ABANDONED"				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

March 25, 1958
 (Date)

Company or Operator W. B. WEAVER

Address P.O. Box 588 - Odessa, Texas

Name W. B. Weaver

Position or Title Agent