

## NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)	<b>X</b>	NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION  
SANTA FE, NEW MEXICO

Monument, New Mexico

(Place)

January 25, 1962

(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the B. HardinAmerada Petroleum Corporation

(Company or Operator)

Well No. 2 in N

(Unit)

SE  $\frac{1}{4}$  SW  $\frac{1}{4}$  of Sec. 18, T. 18-S, R. 38-E, NMPM., Hobbs Pool

(40-acre Subdivision)

Lea

County.

## FULL DETAILS OF PROPOSED PLAN OF WORK

(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

4225' TD - We plan to pull rods & tbg. Notch 4-3/4" open hole from 4215 to 4225', run 3" Tbg. with packer & fracture open hole with 20,000 gals. lease crude & 4500# of 12/20 walnut hulls with 1/20th lb. of Mark II adomite per gal. & scale inhibitor added. Swab test & if unsuccessful, set bridge plug at 4190' with 1 sack cement on top, perforate 5 1/2" OD Csg. liner ~~from~~ with two shots each at 3992', 4000', 4015', 4033', 4046' and 4052' (by Gamma Ray). Acidize these perforations with 500 gals. acid & swab test. If necessary, frac with 10,000 gals. crude oil, 2250# of 12/20 walnut hulls & 500# Mark II Adomite with scale inhibitor ~~and~~ added, using casing ball sealers. Swab, rerun rods, Pump & tubing & resume production.

Approved January 25, 19 62  
Except as follows:Approved  
OIL CONSERVATION COMMISSIONBy [Signature]Title [Signature]Amerada Petroleum Corporation

Company or Operator

By [Signature]Position District Superintendent

Send Communications regarding well to:

Name Amerada Petroleum CorporationAddress Drawer "D", Monument, New Mexico