

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL		REPORT ON RECOMPLETION OPERATION		REPORT ON SAND-OIL, (Other SQUEEZE, ACIDIZE	X

December 15, 1954

(Date)

Monument, New Mexico

(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Amerada Petroleum Corporation

(Company or Operator)

B. Hardin Lease

(Lease)

McAdams Well Service

(Contractor)

Well No. 3 in the NW 1/4 SW 1/4 of Sec. 18

T 18-S, R 38-E, NMPM, Hobbs Pool, Lea County.

The Dates of this work were as follows: 9-14-54 to 10-12-54

Notice of intention to do the work (was) (~~was not~~) submitted on Form C-102 on October 8, 1954, 1954.

(Cross out incorrect words)

and approval of the proposed plan (was) (~~was not~~) obtained.

4040' D.O.D.

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Pulled rods, pump and tubing. Ran Lane Wells Gamma Ray and Neutron Surveys. Tested casing with 2000# - OK. Squeezed open hole from 4011' to 4085' with 225 sacks regular diesel oil cement. Drilled out cement to 4040'. Perforated 7" OD casing from 3980' to 4011' with 124 jet shots. Acidized 7" OD casing perforations from 3980' to 4011' with 300 gallons Halliburton 15% LST acid with MCA added. Sand-oiled 7" OD casing perforations from 3980' to 4011' and open hole from 4011' to 4040' with 6000 gallons Famariss 24 gravity oil and 6000# sand. Swabbed back load and acidized 7" OD casing perforations from 3980' to 4011' and open hole from 4011' to 4040' with 200 gallons 15% LST acid. Tested by swabbing.

Witnessed by R.J. Brakey

(Name)

Amerada Petroleum Corporation

(Company)

Farm Boss

(Title)

Approved OIL CONSERVATION COMMISSION

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name M. Smith

Position Foreman

Representing Amerada Petroleum Corporation

Address Drawer D - Monument, New Mexico

(Title)

(Date)