

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form O-103
Revised 10-1-75

5a. Indicate Type of Lease	
State ☐	Fee ☒
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO SEEPER OF PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM O-121) FOR SUCH PROPOSALS.)

CIL WELL ☒	CAS WELL ☐	OTHER ☐
Name of Operator SHELL WESTERN E&P INC.		
Address of Operator P. O. BOX 576, HOUSTON, TEXAS 77001 (WCK 4435)		
Location of Well UNIT LETTER <u>P</u> <u>330</u> FEET FROM THE <u>SOUTH</u> LINE AND <u>990</u> FEET FROM THE <u>EAST</u> LINE, SECTION <u>18</u> TOWNSHIP <u>18-S</u> RANGE <u>38-E</u> N.M.P.M.		

7. Unit Agreement Name N. HOBBS (G/SA) UNIT
8. Form or Lease Name SECTION 18
9. Well No. 441
10. Field and Pool, or Whist HOBBS (G/SA)

11. Elevation (Show whether DF, RT, GR, etc.) 3662' DF	12. County LEA
---	-------------------

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data.
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPER. ☐	PLUG AND ABANDONMENT ☒
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOB ☐	OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- 10-19-87: Run CBL/VDL/CCL/GR from PBTD (3814') to surf under 0 psi. Run CBL from PBTD to 2600' under 500 psi. TOC @ 2814'. RIH to 3812' & spot 10#/gal mud to 3260'. Spot 30 sx Cls "C" cmt + 2% CaCl₂ from 3260' to 3195'.
- 10-20-87: Spot 10#/gal mud from 3195' to 2715'. Spot 8 sx Cls "C" cmt from 3195' to 3160'. Spot 80 sx Cls "C" cmt across bad csg interval 2715' - 2409'. WOC 4 hrs. Tagged TOC @ 2553'. Spot 50 sx Cls "C" cmt + 1/4#/sk flocele + 2% CaCl₂ from 2553' to 2380'.
- 10-21-87: Circ'd 10# mud from 2380' to 240'. Set CIBP @ 2257'. Perf'd csg @ 250' (2 JSPF). Etab circ & pmpd 100 sx Cls "C" cmt + 2% CaCl₂, sqzd 50 sx into fm & left 50 sx inside 8-5/8" csg. Did not circ cmt to surf. Cut off csg below GL, welded on steel plate & installed P&A marker.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

APPROVED BY A. J. FORE TITLE SUPERVISOR REG. & PERMITTING DATE OCTOBER 29, 1987

APPROVED BY Boz (Signature) TITLE OIL & GAS INSPECTOR DATE NOV 19 1987

RECEIVED
NOV 2 1987
OCD
HOBBS OFFICE