

## OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELLS

MAY 7 1946

RECEIVED

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after completion of the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below:

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL	<b>X</b>		

Midland, Texas

May 6, 1946

Place

Date

OIL CONSERVATION COMMISSION,  
SANTA FE, NEW MEXICO.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the

Humble Oil & Refining Company Federal Bowers "B" Well No. 2 in the  
Company or Operator Lease

NE/4 of SE/4 of Sec. 20, T. 18-S, R. 38-E, N. M. P. M.,  
Hobbs Field, Lea County.

The dates of this work were as follows: April 12, 1946 to May 6, 1946Notice of intention to do the work was (~~submitted~~) submitted on Form C-102 on April 1, 1946 19and approval of the proposed plan was (~~obtained~~) obtained. (Cross out incorrect words.)

## DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Cemented bottom of hole with 75 sx. El Toro cement. Shot 7" casing at 3000', failed to pull. Shot 7" casing at 2800', pulled 95 joints. Filled hole with mud-laden fluid to 2800'. Cemented from 2800' to 2500' with 50 sx. El Toro cement. Shot 10-3/4" casing at 980', pulled 34 joints. Filled hole with mud-laden fluid from 2500' to 980'. Cemented hole from 980' to 780' with 50 sx. El Toro cement. Filled hole with mud-laden fluid from 780' to 300'. Cemented hole from 300' to surface with 150 sx. El Toro cement. Installed 4" marker at abandoned well site.

Witnessed by \_\_\_\_\_  
Name Company Title

Subscribed and sworn before me this 6

I hereby swear or affirm that the information given above is true and correct.

day of May, 19 46

Name \_\_\_\_\_

Position Division SuperintendentRepresenting Humble Oil & Refining Company  
Company or OperatorMy commission expires June 1, 1947Address Box 1600, Midland, Texas

Remarks:

Name

Title