

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

## OIL CONSERVATION DIVISION

2040 Pacheco St  
Santa Fe, NM 87505

|  |
|--|
| WELL API NO.   |
| Indicate Type of Lease<br>STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>   |
| State Oil & Gas Lease No.  |
| Lease Name or Unit Agreement Name<br>North Hobbs G. S/A Unit   |
| Well No.<br>121  |
| Pool name or Wildcat<br>Hobbs; G. S/A  |
| Well Location<br>Unit Letter <u>E</u> : <u>1980</u> Feet From The <u>North</u> Line and <u>660</u> Feet From The <u>West</u> Line<br>Section <u>20</u> Township <u>18S</u> Range <u>38E</u> NMPM <u>Lea</u> County |
| Elevation (Show whether DF, RKB, RT, GR, etc.)   |

**SUNDRY NOTICES AND REPORTS ON WELLS**  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

Type of Well:  
OIL WELL ☒ GAS WELL ☐ OTHER

Name of Operator  
Occidental Permian

Address of Operator  
1710 W Stanolind Rd. Hobbs, NM 88240

Well Location  
Unit Letter E : 1980 Feet From The North Line and 660 Feet From The West Line  
Section 20 Township 18S Range 38E NMPM Lea County

Elevation (Show whether DF, RKB, RT, GR, etc.)

11

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

### NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐  
OTHER: ☐

### SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☒  
CASING TEST AND CEMENT JOB ☐  
OTHER: ☐

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Well TA'D 3-94 CIBP set @ 4150', capped with 35' of cement.

1/2/01 Tagged CIBP @ 4115'. Circ. well with MLF

Plug # 1 1/2/01 Spot 25 sks of cement @ 3985'. Tagged @ 3790'

Plug # 2 Perf @ 2750' Pressured up on perfs to 1000 psi-Held. Notify OCD Spot 40 sks of cement @ 2850' Tagged @ 2575'

Plug # 3 Perf @ 1815' Pressured up on perfs to 1000 psi-Held. Notify OCD. Spot 30 sks of cement @ 1870'. Tagged @ 1676'

Plug # 4 Found hole in casing @ 550'. Set CICR @ 500'. Squeezed 50 sks of cement ISITP= 250 ps. Capped CICR with 30' of cement. Tagged @ 470'

Plug # 5 Perf @ 310' Pressured up on perfs to 1000 psi-Held. Notify OCD. Spot 80 sks of cement @ 365'- surface

Cut off wellhead & anchors 4' BGL. Capped well with steel plate. Due to well in township- weld legal discription onto plate, and weld plate to well 4' BGL

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Jack Shelton TITLE Key Energy DATE 1-20-01

TYPE OR PRINT NAME Robert Gilbert TELEPHONE NO

(This space for State Use)

APPROVED BY Ed Gonzalez TITLE Field Rep DATE 2-14-02

CONDITIONS OF APPROVAL - ANY

GWW