

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

## OIL CONSERVATION DIVISION

2040 Pacheco St.  
Santa Fe, NM 87505

WELL API NO. 30-025-07386
Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
State Oil & Gas Lease No.
Lease Name or Unit Agreement Name North Hobbs G SA Unit
Well No. 431
Pool name or Wildcat Hobbs G SA

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	
Name of Operator Occidental Permian	
Address of Operator 1710 W Stanolind Rd Hobbs NM 88240	
Well Location Unit Letter <u>I</u> : <u>1650</u> Feet From The <u>South</u> Line and <u>660</u> Feet From The <u>East</u> Line Section <u>20</u> Township <u>18S</u> Range <u>38E</u> NMPM <u>Lea</u> County	
Elevation (Show whether DF, RKB, RT, GR, etc.) 3644' Gr.	

11

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

### NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐  
OTHER: ☐

### SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS ☐ PLUG AND ANBANDONMENT ☒  
CASING TEST AND CEMENT JOB ☐  
OTHER: ☐

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Well TA'D 5/1989 W/ CIBP set at 4062' TOC @ 4037'. CICR set @ 3196'. Sq'd 50 sks of cement Cap W/ 4 sks

1/11/01 Tagged CICR @ 3156'. Circ. well W/ M.L.F.

1/11/01 Plug # 1 Perf. @ 2765'. Pressured up on perms to 1000 psi- Held. Spot 25 sks of cement @ 2821'. Tag @ 2575'

1/11/01 Plug # 2 Perf. @ 1790'. Pressured up on perms. to 1000 psi- Held. Spot 25 sks of cement 1862'. Tag @ 1677'

1/12/01 Plug # 3 Perf @ 355'. Circ. 150sks of cement down 5 1/2" though perms, up annulus to surface.

Cut off wellhead & anchors 4' BGL. Cap well with steel plate. Due to well in township, legel discription welded on plate, plate welded to well 4' BGL. Location cleaned

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Jack Shelton TITLE Key Energy DATE 1-13-01  
(Robert Gilbert)

TYPE OR PRINT NAME TELEPHONE NO

(This space for State Use)

APPROVED BY [Signature] TITLE fld Rep DATE 2-14-02

CONDITIONS OF APPROVAL IF ANY

C-u/w/