

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

HOBBS OFFICE 000

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK	<input checked="" type="checkbox"/>	NOTICE OF INTENTION TO SET LINER	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO SQUEEZE	<input checked="" type="checkbox"/>	NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE	<input checked="" type="checkbox"/>	NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Hobbs, New Mexico
(Place)

November 28, 1956
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the

Gulf Oil Corporation Gertrude Morris et al Well No. 1 in 0
(Company or Operator) (Unit)
SW 1/4 NE 1/4 of Sec. 21, T. 18-S, R. 38-E, NMPM., Undesignated Pool
Lee County.

FULL DETAILS OF PROPOSED PLAN OF WORK

(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

It is proposed to plug back, run liner, perforate liner and test perforated intervals as follows:

- Set 65 sacks cement plug from 11211-11050', 23 sacks cement plug from 10850-10800', 57 sacks cement plug from 9275-9125', 38 sacks cement plug from 8650-8550', 57 sacks cement plug from 8250-8100', 38 sacks cement plug from 7500-7400', 19 sacks cement plug from 6900-6850', 19 sacks cement plug from 6300-6250'; heavy mud will be placed in intervals of cement plugs.
- Run 5-1/2" OD casing liner and set at approximately 6250-4277'.
- Perforate and test following intervals in 5-1/2" liner:
Blinbry 6152-6180'
Paddock 5755-5775'
San Andres 4475-4500' and 4335-4360'
Grayburg 4250-4275'
Queen 3680-3710', 3755-3790' and 3830-3855'
Formation will be squeeze cemented on abandonment.

Approved....., 19.....
Except as follows:

Approved
OIL CONSERVATION COMMISSION

By R. F. Montgomery
Title PRODUCTION MANAGER

Gulf Oil Corporation.

Company or Operator

By

Position

Area Supt. of Prod.

Send Communications regarding well to:

Name

Gulf Oil Corporation

Address

Box 2167, Hobbs, New Mexico