

## NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## NOTICE OF INTENTION TO DRILL

Notice must be given to the Oil Conservation Commission or its proper agent and approval obtained before drilling begins. If changes in the proposed plan are considered advisable, a copy of this notice showing such changes will be returned to the sender. Submit this notice in triplicate. One copy will be returned following approval. See additional instructions in Rules and Regulations of the Commission.

Hobbs, New Mexico,

November 15, 1935

OIL CONSERVATION COMMISSION,  
Santa Fe, New Mexico

Gentlemen:

You are hereby notified that it is our intention to commence the drilling of a well to be known as

**Oil Well Drilling Company****Morris**Well No. **1**in **SW 1/4 SE 1/4**

of Sec. **21**, T. **18S**, R. **38E**, N. M. P. M., **Hobbs** Field, **Lee** County.

N.

The well is **350** feet [N.] of the **South** line and **2310** feet[E.] [W.] of the **East** line of **section 21, T18S, R38E,**

(Give location from section or other legal subdivision lines. Cross out wrong directions.)

If state land the oil and gas lease is No. \_\_\_\_\_ Assignment No. \_\_\_\_\_

If patented land the owner is **James W. Morris**Address **Capitan, New Mexico**

If government land the permittee is \_\_\_\_\_

Address \_\_\_\_\_

The lessee is **Oil Well Drilling Company**Address **1123 Athletic Club Building, Dallas, Texas**

We propose to drill well with drilling equipment as follows: \_\_\_\_\_

**Rotary Tools**

The status of a bond for this well in conformance with Rule 39 of the General Rules and Regulations of the Commission is as follows: **\$10,000. surety company bond to cover all wells drilled or to be drilled.**

We propose to use the following strings of casing and to land or cement them as indicated:

Size of Hole	Size of Casing	Weight Per Foot	New or Second Hand	Depth	Landed or Cemented	Sacks Cement
<b>16"</b>	<b>12 1/2"</b>	<b>50 lbs.</b>	<b>Good second hand.</b>	<b>250 to 300 feet.</b>	<b>cemented to bottom of cellar.</b>	<b>200</b>
<b>8 1/2"</b>	<b>7"</b>	<b>24 lb. SS</b>	<b>New</b>	<b>Approx. 4000'</b>	<b>(see notation below)</b>	<b>318 Top 150 Bottom</b>

If changes in the above plan become advisable we will notify you before cementing or landing casing. We estimate that the first productive oil or gas sand should occur at a depth of about **4240** feet.

Additional information: **7" casing to be cemented using Halliburton multiple 2 stage job, 150 sacks at bottom of 7", 318 sacks from top of salt to bottom of surface casing. Before cementing 7", good clean mud weighing approximately 11 lbs. to be circulated around pipe leaving good body of mud between the two stages in the salt proper.**

Approved \_\_\_\_\_, 19 \_\_\_\_\_  
except as follows:

Sincerely yours,

**Oil Well Drilling Company**By **W. E. Cunningham**  
Company or OperatorPosition **Secretary**

Send communication regarding well to

Name **Oil Well Drilling Company**Address **Hobbs, New Mexico.**

OIL CONSERVATION COMMISSION,

By **F. J. [Signature]**

Title \_\_\_\_\_

