

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or its agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of notice by checking below:

NOTICE OF INTENTION TO TEST CASING SHUT-OFF		NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL	
NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING	
NOTICE OF INTENTION TO REPAIR WELL		NOTICE OF INTENTION TO PLUG WELL	
NOTICE OF INTENTION TO DEEPEN WELL		Plugging well back	XXXXXX

Hobbs, New Mexico.

March 22nd, 1936.

Place

Date

OIL CONSERVATION COMMISSION,
Santa Fe, New Mexico.

Gentlemen:

Following is a notice of intention to do certain work as described below at the

GULF OIL CORPORATION OF PENNSYLVANIA

GYPSY DIVISION

Steve Taylor

Well No. 1

in NE/4

Company or Operator

Lease

of Sec. 24, T. 18s, R. 38s, N. M. P. M., Hobbs, Field,

Lea.

County.

FULL DETAILS OF PROPOSED PLAN OF WORK

FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION

Drilled the well to 4883', set packer at 4810' and tested, unable to lower the water. Cemented back with 16 sax cement by the Halliburton Cementing Process and filled back to 4760'. Set packer at 4706' and tested, unable to lower water below 3500' from top. Cemented back with 24 Sax Cement and found cement at 4606'. Set packer at 4590' and swabbed well down to bottom but water came in as fast as could be swabbed. Cemented well back with 5 sax by Halliburton and filled up to 4590', lost bailer while bailing and parted the 5-1/2" Casing fishing for the bailer. Tore out rotary tools and rigged up standard tools. Bailed hole down and same made 3 1/2 barrels water per hour. Drove Wood limit plug and 300# lead wool to 4590' and tested, still making 1 1/2 bailer water per hour. Drove 400# Lead wool filling hole back to 4585'. The water not completely shut off.

Shot well with 30-Qts from 4538' to 4550', plain anchor on bottom and Zero hour bomb on top. Cleaned well out to bottom and hole was dry.

Will ask for permission to plug and abandon the well.

DUPLICATE

MAR 26 1936

Approved _____, 19_____
except as follows:

GULF OIL CORPORATION OF PENNSYLVANIA
GYPSY DIVISION

Company or Operator

By

Position

District Superintendent

Send communications regarding well to

Name

O.C. Cummings.

Address

Hobbs, New Mexico.

OIL CONSERVATION COMMISSION,

By

Title

Oil & Gas Inspector

1948-1949

1948-1949

1948-1949

1948-1949

1948-1949

1948-1949

1948-1949

1948-1949

1948-1949

1948-1949

1948-1949

1948-1949

1948-1949

1948-1949

1948-1949

1948-1949

1948-1949

1948-1949

1948-1949

1948-1949

1948-1949

1948-1949

1948-1949

1948-1949

1948-1949

1948-1949

1948-1949

1948-1949

1948-1949

1948-1949

1948-1949

1948-1949

1948-1949

1948-1949

1948-1949

1948-1949

1948-1949

1948-1949

1948-1949

1948-1949

1948-1949

1948-1949

1948-1949

1948-1949

1948-1949

1948-1949

1948-1949

1948-1949

1948-1949