NEW MEXICO STATE LAND OFFICE

OFFICE OF THE STATE GEOLOGIST

SANTA FE, NEW MEXICO

MISCELLANEOUS NOTICES

Submit this notice in triplicate to the State Geologist or proper Oil and Gas Inspector at least five days before the work specified is to begin. A copy will be returned to the sender on which will be given the approval with any modifications considered advisable or the rejection by the State Geologist or Oil and Gas Inspector of the plan submitted. The plan as approved should be followed and work should not begin until approval is obtained.

NOTICE OF INTENTION	Indicate nature of	NOTICE OF INTENTION TO PULL OR
		NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING
NOTICE OF INTENTION	TO REPAIR WELL	
NOTICE OF INTENTION TO DEEPEN WELL		AUID TREAT WILL
		110bbs, N. 1., 10/15/34.
Mr.J.D. Numcer, C	. C.Insp State Geolog	
-Santa-Ee, N. Mez	., Jarlsbad.	
Following is a no	tice of intention to do ce	rtain work as described below at the
corp.,	Sanger	Well No. 1 in Sal Stal
of Sec. 27	r. 18 S R. 38	A.N. M. P. M., Hobbs
·	LeaCo	
The vell	will be treated w	/2000 gal. acid by Double. (il
will be jumped acid will then from hole will has been shut :	will be treated w down tubing until be pumped into we then be pumped do in for 72hrs. it	
will be sumped arid will then from hole will	will be treated word down tubing untill be pumped into we then be pumped doing for 72hrs. it	/2000 gal. acid by Detall. (il. 1 pressure declines to zero. The ell. Sufficient oil to flush acid own tog. and casing. After the well will be opened up and given an (aficial)
will be sumped and will then from hole will has been shut largetion fest	will be treated wo down tubing until be pumped into we then be pumped do in for 72hrs. it	/2000 gal. acid by Dowell. (il. 1 pressure declines to zero. The ell. Sufficient oil to flush acid own thg. and casing. After the well will be opened up and given an (aficial) 30.K. Shell Tetroloum Sorp.
will be umped and will then from hole will has been shut the from the trong transfer the transfer tran	will be treated wo down tubing until be pumped into we then be pumped do in for 72hrs. it	/2000 gal. acid by Dowell. (il lorescure declines to zero. The ell. Sufficient oil to flush acid own tog. and casing. After the well will be opened up and given an (aficial second seco
will be umped and will then from hole will has been shut from tion fest Approved	will be treated wo down tubing until be pumped into we then be pumped do in for 72hrs. it	/2000 gal. apid by Dowell. (il. l pressure declines to zero. The ell. Sufficient oil to flush apid own thg. and casing. After the well will be opened up and given an (Efficial 30.K. Shell Tetroloum Corp. Recommy obspersance.
will be umped and will then from hole will has been shut largetion Test Approved	will be treated wo down tubing until be pumped into we then be pumped do in for 72hrs. it	/2000 gal. acid by Dowell. (il. 1 pressure declines to zero. The ell. Sufficient oil to flush acid own thg. and casing. After the well will be opened up and given an (aficial) 30.K. Shell Tetroloum Sorp.
will be umped and will then from hole will has been shut from tion fest Approved	will be treated wo down tubing until be pumped into we then be pumped do in for 72hrs. it	Jacob gal. acid by Double. (il pressure declines to zero. The ell. Sufficient oil to flush acid own tog. and casing. After the well will be opened up and given an (Fficial So. K. Shell Fetroloum Corp. By District Engineer