

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-	7. Unit Agreement Name N. HOBBS (G/SA) UNIT
2. Name of Operator SHELL WESTERN E&P INC.	8. Farm or Lease Name SECTION 28
3. Address of Operator P. O. BOX 991, HOUSTON, TX 77001	9. Well No. 331
4. Location of Well UNIT LETTER J 2310 FEET FROM THE EAST LINE AND 1650 FEET FROM THE SOUTH LINE, SECTION 28 TOWNSHIP 18-S RANGE 38-E N.M.P.M.	10. Field and Pool, or Wildcat HOBBS (G/SA)
15. Elevation (Show whether DF, RT, GR, etc.) 3649' GR	12. County LEA

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data.
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input checked="" type="checkbox"/> WSO & ACIDIZE

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input type="checkbox"/>	
OTHER <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1. Clean out to 4280'.
2. Set 4" RBP @ 4140'±. Spot 2 sx (200#, 20'±) sand on top of RBP.
3. Set 4" CICR @ 4020'±. Squeeze San Andres I perms 4081' to 4193' w/50 sx Class "C" cmt w/2% CaCl₂ and 0.3% Halad 4. WOC 24 hours.
4. Drill out CICR and cement. Pressure test squeeze to 500 psi for 15 minutes.
5. Acidize the San Andres II (4152' to 4171') and IIIU (4185' to 4268') using 3500 gals 15% HCl-NEA inhibited.
6. Install production equipment and return well to production.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED J. Curtis Fore A. J. FORE

TITLE SUPERVISOR REG. & PERMITTING

DATE MARCH 7, 1984

ORIGINAL SIGNED BY JERRY SEXTON

APPROVED BY DISTRICT SUPERVISOR

TITLE _____

DATE MAR 13 1984

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED
MAR 12 1984
CCT
HOBBS OFFICE